

# Dell Avamar 19.10 Release Notes

This document describes new and changed features, resolved issues, known issues, and supplemental information about the Avamar 19.10 release.

**Current Release Version:** 19.10

**Release Type:** Major (MA)

Topics:

- [Revision history](#)
- [Avamar overview](#)
- [New features and changes](#)
- [Changed features](#)
- [Resolved issues](#)
- [Known issues](#)
- [Environment and system requirements](#)
- [International language support](#)
- [Technical notes](#)
- [Documentation](#)
- [Installation and upgrade considerations](#)
- [Where to get help](#)

## Revision history

The following table presents the revision history of this document:

**Table 1. Revision history**

Revision	Date	Description
A01	February 2024	Updated the following sections: <ul style="list-style-type: none"><li>• Enhancing support</li><li>• Installation and upgrade considerations</li></ul>
A00	January 2024	First release of this document for Avamar 19.10

## Avamar overview

Avamar is backup and recovery software with integrated data deduplication technology. Avamar solves the challenges that are associated with traditional data protection, enabling fast, reliable backup and recovery for remote offices, VMware environments, Data Domain and Cloud Tier, and data center LANs.

Unlike traditional solutions, Avamar reduces the size of backup data at the source—before it transfers across the network and stores to disk. As a result, Avamar delivers fast, efficient daily full backups despite slow or congested infrastructure, and data encryption for added security. Avamar uses patented RAIN technology for high availability, and a scalable grid architecture enables you to upgrade capacity and performance when necessary.

### NOTE:

- Any references to the Data Domain systems and the Data Domain devices in the document indicate PowerProtect DD appliances.
- This Dell product utilizes an embedded Linux distribution, which is licensed to Dell. This embedded Linux is authorized to be used to operate only Dell products.

# New features and changes

The following sections provide information about the new features and changes in Avamar 19.10:

**Table 2. New features in Avamar 19.10**

Functional area	Feature description	Summary of benefits
AUI	<p>Added an information button in the <b>Replace Private Entry</b> wizard. This information button provides a high-level explanation about the Private Key, Certificate, and Chain of trusted root certificates.</p> <p>To see this wizard in the AUI, go to <b>Administration &gt; System</b> window. Select <b>Certificate</b> tab and click <b>Private Key</b> tab. Click <b>+Replace</b>, the <b>Replace Private Entry</b> wizard is displayed.</p>	The explanation that is provided in the information button helps you to understand the importance of key and certificates.
AUI	Added support for the Korean language.	Not applicable
AUI	Added support for three new columns, <b>Backup Lock</b> , <b>Backup Lock Expiry Date</b> , and <b>Immutable Backup Configuration</b> within the backup list pane in the <b>Backup</b> tab.	You can view period lock and immutable backup related statuses in the AUI.
AUI	Added support to add and update SMTP mail server details in the <b>Setting</b> window.	Starting from Avamar 19.10, you can update the SMTP mail server configuration details from the AUI.
Avamar Server	Added support for a new option <code>[avtar]repl-metadata-only</code> .	When the option is set to <code>true</code> , it replicates only metadata during replication.
Avamar Server	Added support for a new option <code>[replscript]copyuser</code> to enable or disable the mechanism that copies admin, nonadmin, user created, or system default user accounts from source Avamar system to <code>REPLICATE</code> domain of destination Avamar system during the replication process.	<p>When you disable the <code>[replscript]copyuser</code> option or set it to <code>false</code>, the user accounts from the source Avamar system are not copied to the <code>REPLICATE</code> domain of the destination Avamar system.</p> <p>When you enable <code>[replscript]copyuser</code> option or set it to <code>true</code>, the user accounts from the source Avamar system are copied to <code>REPLICATE</code> domain of the destination Avamar system which represents the existing behavior.</p> <div> <p><b>NOTE:</b></p> <ul style="list-style-type: none"> <li>By default, the <code>[replscript]copyuser</code> option is set to <code>true</code>.</li> <li>When the <code>[replscript]fullcopy</code> option is set to <code>true</code>, Avamar follows the existing behavior for this option.</li> </ul> </div>
Avamar Server	Added support for Data Domain Retention Lock (DDRL) in governance mode.	<ul style="list-style-type: none"> <li>When you enable governance mode in Avamar, you can lock the backup data in the Data Domain server by using DDRL in governance mode.</li> <li>Avamar supports period lock feature in governance mode.</li> <li>Compliance mode and governance mode support <b>No end date</b> option in <b>Retention Policy Settings</b> with period lock.</li> </ul>

**Table 2. New features in Avamar 19.10 (continued)**

Functional area	Feature description	Summary of benefits
		<ul style="list-style-type: none"> <li>Governance mode supports all plug-ins.</li> </ul>
Data Domain	Added support for the DD Boost API of the DD OS 7.12	Not applicable
Granular level recovery	Added support for ItemPoint 8.9.2	Not applicable
MCS	Added <b>Password Validation</b> tab with <b>Password Expiry</b> and <b>Warning Days</b> fields in the Avamar Installation Manager.	The feature allows you to set the number of days for password expiry and the ability to show a warning message for password expiry.
Virtualization	Added support for improved proxy deployment.	The feature allows you to ignore new proxy entries which are not fully configured and only allows fully configured proxy definitions. This allows a partial use of the Recommendation only for the required ESXi clusters.
Virtualization	Added support for a new option <code>force_rdm_backup_failure</code> to enable or disable the warning message that displays <code>Virtual machine client contains disks that cannot be backed up or restored</code> . By default, the warning message is disabled.	When you enable the <code>force_rdm_backup_failure</code> option, the warning message notifies you of the potentially unprotected data.
Virtualization	Added support for FLR, when an LVM volume group span two or more Linux GPT partitions.	Not applicable
Hyper-V VSS	Added support for Azure Stack HCI version 22H2 with Avamar 19.9 and later.	Not applicable
Virtualization	Added support to configure the additional network interface on the proxy.	Not applicable

## Changed features

The following table lists the changed features in this release:

**Table 3. Changed features in Avamar 19.10**

Functional area	Feature description	Summary of benefits
Dell Connectivity	Dell Connectivity is the replacement of ConnectEMC. Dell Connectivity is a program that runs on the Avamar server and sends information to Avamar support.	Dell Connectivity is configured to send alerts for high priority events as they occur and reports once daily. When you upgrade to the Avamar 19.10, ConnectEMC is removed, and the existing connectivity disconnects. Dell Connectivity is also known as Embedded Service Enabler (ESE).
Security	The password complexity rules for operating system user accounts have changed. These rules determine the length and reuse of passwords.	The change in password rules prevents GSAN failure, saving time previously spent on upgrades due to GSAN failure.
Security	Added authorization requirement before viewing the list of API commands.	The authorization window appears automatically when you open the Swagger UI. This feature change restricts the user to view the list of RESTful API commands before authentication. User can view or run the

**Table 3. Changed features in Avamar 19.10 (continued)**

Functional area	Feature description	Summary of benefits
UI	Removed the selection of <b>Disabled</b> checkbox by default while configuring the properties for backup groups.	API commands only after authentication based on the user access level.  With this change in the feature, the newly created backup groups are enabled by default. As a result, the backups are triggered as per the schedule.
User Interface	The Avamar UI displays the updated branding of Dell Technologies as the company brand and Dell as the product brand.	Not Applicable

## Operating system enhancements

Avamar 19.10 includes an upgrade for all supported platforms to the SUSE Linux Enterprise Server (SLES) 12 SP5 operating system. This upgrade replaces the previous SLES 11 and SLES 12 operating systems.

**NOTE:** All routes to Avamar 19.4 and later require the deployment of, or upgrade to, SLES 12 SP5. The new operating system is a required component of Avamar 19.4 and later.

The operating system upgrade does not affect the functionality or interfaces of the Avamar software. However, take note of the following important points:

- The Avamar platform operating system security rollup supports Avamar servers that run SLES 12 SP5 starting with release 2020R1.
- The upgrade changes some underlying operating system commands, such as the move from `systemv` to `systemd`.
- The upgrade also updates some underlying libraries and dependencies.
- All new installations of Avamar 19.4 and later, and SLES 12 deploy with a 1 GB `/boot` partition to improve compatibility with future kernel upgrades. Upgrades from SLES 11 preserve the existing 100 MB `/boot` partition.

## Prerequisites

Review the following items when you create your deployment or upgrade plan:

- All nodes in the server must run one of the following operating systems:
  - SLES 12 SP5
  - SLES 12 SP4
  - SLES 11 SP4
  - SLES 11 SP3
  - SLES 11 SP1
- Avamar 7.5.1 or later is a prerequisite for the upgrade to Avamar 19.10.

If the server or NDMP accelerator node runs an older release, upgrade to a supported version before you start the upgrade to Avamar 19.4 and later.

- Supported hardware platforms:
  - Gen4T
  - Gen5A

## New installations and deployments

New instances of AVE 19.4 and later for all supported virtual environments deploy with SLES 12 SP5. New VMware proxy instance also deploys with SLES 12 SP5.

New installations of the Avamar Data Store (ADS) Gen4T and Gen5A platforms must have SLES 12 SP5 loaded before software installation. The existing Avamar software installation procedures for the ADS do not change.

New installations of NDMP accelerator nodes, whether physical or virtual, must have SLES 12 SP5 loaded before software installation. The existing NDMP accelerator software installation procedures do not change.

## Upgrades from previous versions

**NOTE:** Consider the following:

- Customers running Avamar versions 7.5.1, 18.1.x, 18.2.x, 19.1.x, 19.2.x, 19.3.x, 19.4.x, 19.4.0.124, 19.7.x, 19.8.x, and 19.9.x can upgrade to 19.10.
- Before you upgrade, verify that the Avamar server, or NDMP accelerator node meets the prerequisites.
- Upgrades from older releases of Avamar or the NDMP accelerator client software might require intermediate upgrades to a supported Avamar release and operating system. Ensure that your upgrade plan includes any necessary incremental steps, and that the server or NDMP accelerator node meets the prerequisites for any intermediate upgrades.
- You cannot upgrade an Avamar server to 19.10 if it uses Blowfish for its data-at-rest encryption. Instead, install a new 19.10 server and migrate the data from the old server.

The Avamar software upgrade workflow package integrates both the operating system upgrade to SLES 12 SP5 and the software upgrade to Avamar 19.10. The upgrade workflow migrates the operating system and Avamar software configurations and then replaces the existing system partitions.

Initial startup might take longer as the upgrade workflow installs necessary drivers and firmware, and configures new packages. The upgrade workflow also takes checkpoints and performs health checks before and after the upgrade. The operating system upgrade process is the same for AVE and for ADS single-node and multi-node servers.

For NDMP accelerator nodes, the process is similar. However, in this case, the Avamar accelerator upgrade workflow package contains the new operating system and the new accelerator software.

You cannot upgrade VMware proxies from one operating system to another by using the ISO file. Instead, remove the existing proxies and use the Proxy Deployment Manager (PDM) to deploy replacement Avamar 19.10 proxies. Remove any proxies that you manually deployed. The *Avamar for VMware User Guide* provides more information.

## FIPS mode

The Avamar software upgrade workflow disables Federal Information Processing Standard (FIPS) mode. If FIPS mode is enabled before the upgrade, you must reenable FIPS mode after the upgrade completes.

**NOTE:** The upgrade workflow disables FIPS if the original version is 19.1. If the original version before upgrade is 19.3 and later, upgrade workflow does not disable FIPS.

The *Avamar Product Security Guide* provides more information about FIPS mode.

## Determine the installed Avamar version

Before you upgrade, determine the version of the installed Avamar so that you can plan the upgrade path.

You can also review the package installation history through the Avamar Installation Manager. The *Avamar Administration Guide* provides more information.

### 1. Through the AUI:

For Avamar 18.1 and later, the AUI provides the preferred graphical method.

- a. Log in to the AUI.
- b. In the AUI header pane, click ⓘ.

The **About** dialog box opens, and lists the installed Avamar version.

### 2. Through the command line:

Where the AUI is not available, verify the Avamar component versions with the following commands.

- a. Log in to the server as admin.
- b. Check the MCS version by typing the following command:

```
mcserver.sh --version
```

An output similar to the following appears:

```
version: 19.1.0-38
```

- c. Check the gsan version by typing the following command:

```
gsan --version
```

An output similar to the following appears:

```
version:      19.1.0-38
build date:   Apr 25 2019 19:23:45
```

- d. Check the `avtar` version by typing the following command:

```
avtar --version
```

An output similar to the following appears:

```
version:      19.1.0-38
build date:   Apr 25 2019 19:32:16
```

Verify that the Avamar component versions match.

## Compatibility updates

The updated software and database compatibility information is provided in the E-LAB Navigator at <https://elabnavigator.dell.com/eln/elhome>.

## Resolved issues

The following table lists the issues that are fixed in Avamar 19.10 release after they were observed in previous releases:

**Table 4. Resolved issues**

Issue ID	Functional area	Description
38093	vCloud	VCP Manager service not running after 19.10 DPE upgrade.
38505	vCloud	DPE 19.10 problem with <code>clean-bg-tmp.sh</code> script.
336344	MCS	Disabling paging from the MCS does not work.
36970	MCS	High Priority Events codes changed
337977	MCS	SNMP Traps issue : error AVAMAR-MCS-MIB::lastActivityPlugInName: Value out of range
337023	Serviceability	Hide the Jetty version during the Security scans.
337289	Virtualization	After upgrading the Avamar server to 19.7 or 19.8, the FLR is not possible with new proxies.
338759	Serviceability	Permission for <code>/usr/local/avamar/var/mc/server_data/prefs/preferences.dtd</code> are wrongly set.
35613	MCS	Unable to retire the VMware image client when <code>uuid</code> is null.
336183	MCS	Changing certificate process using AUI goes in a loop if any of the operations fails while updating or installing a certificate and never exit.
37484	MCS	<code>clean_db</code> keeps failing after applying MCS HF337055.
338226	Avamar Server	Passwords with more that 20 characters are ignored during upgrade process.

**Table 4. Resolved issues (continued)**

Issue ID	Functional area	Description
338087	Backup	Backup fails if the Isilon fails to create a snapshot. The system restricts to proceed with the restore.
336126	Backup	Full Backup and incremental backup work without any log gap error.
36842	Oracle	Activity status displays as "failed" while Sa control file from the CLI if the database is not mounted.
336115	Security	On the Avamar server, navigating from one user role to another user role using cookies is restricted.
338401	Virtualization	FLR mount fails if the LVM volume group span two or more Linux GPT Partitions.
335950	Security	On the Swagger UI, running RESTful API commands and performing command actions are restricted based on the user access level.
338779	Avamar Server	Compliance mode and governance mode must support no expiry retention mode with period lock.

## Known issues

The following sections describe the known issues in Avamar. Temporary solutions are provided when they are available.

### Avamar server known issues

The following table lists the known issues of Avamar server in this release:

**Table 5. Avamar server known issues**

Issue ID	Subject/Functional area	Description	Workaround/Resolution
	GSAN account	GSAN fails to start while installing OS Rollup 2023 R2 and R3 on the AWS AVE for Avamar versions 19.4,19.7,19.8, 19.9 and 19.10.	N/A
	DPN Services/Tomcat services/NTP	EM Tomcat service goes down while restarting the NTPD services during OS Rollup R1, R2, and R3. This issue is observed only after the OS Rollup is applied for the first time.	Restart Avamar or the DPN services as applicable.
38619	Replication	Replication fails for <code>MCUser</code> and <code>repluser</code> users when the option <code>[replscript] fullcopy</code> is set to <code>true</code> and source and destination Avamar servers have different passwords configured.	Create a replication policy with the <code>root</code> user. You can use the option <code>[replscript] fullcopy</code> with the <code>root</code> user. After the replication completes, you cannot log in to destination Avamar server with <code>MCUser</code> credentials, you can log in using the <code>root</code> user credentials. To solve this issue, use the <code>change-passwords</code> utility in the destination Avamar server and

**Table 5. Avamar server known issues (continued)**

Issue ID	Subject/Functional area	Description	Workaround/Resolution
			set new passwords for operating system user, server user, MCUser, root user, and view user. It is recommended to use a common password for the mentioned roles. The <code>change-passwords</code> utility restarts the administrator server at the end, so you can log in to the destination Avamar server using the new passwords set for the MCUser.
161698	Replication fails with code 157: miscellaneous error code when the hard quota limit exceeds.	The replication must fail with <code>Hard quota limit exceeded</code> error, but instead it fails with code 157: miscellaneous error code.	N/A
46224	Scheduled backups are missed during daylight savings time transitions.	Scheduled backups are missed during daylight savings time transitions.	<p>During days when Daylight Saving Time (DST) transitions occur, if you have backups that are scheduled to run during the following times, the backups do not occur:</p> <ul style="list-style-type: none"> <li>For the Spring DST transition, daily backups that are scheduled during the hour from 2:00 a.m. through 2:59 a.m. do not occur.</li> <li>For the Autumn DST transition, daily backups that are scheduled during the hour from 1:00 a.m. through 1:59 a.m. do not occur.</li> </ul> <p>The interim solution to this problem is to avoid scheduling backups during these time ranges, or to perform a manual backup when the scheduled backup does not occur.</p>
299817 esc 29070	After root-to-root MC restore fails with "clients" violates a foreign key constraint.	MC restore fails with clients violate foreign key constraint after root-to-root replication.	The support team must update db schema with the provided script manually.
309181 esc 34646	<code>mcserver.sh --init</code> fails to run <code>mcrootca</code> successfully and also fails to decrypt passwords for <code>rmi_ssl_keystore_AP/rootAP</code> and <code>viewuserAP</code> .	If you run <code>mcserver.sh</code> with <code>--init</code> or <code>--restore</code> in the incorrect context, directories might be deleted. The <code>mcserver.sh --init</code> command is designed only for internal execution from the workflow framework during a new installation. An error occurs if you run the command manually.	N/A
309554	IPv4 traffic initiated by Avamar in a dual-stack environment	In a dual-stack environment where both Avamar and Data Protection Central (DPC) have IPv4 and IPv6 addresses that are configured, the communication should occur using IPv6 since this is the preferred network. However, IPv4 traffic is observed when Avamar connects to the DPC for the first time.	To avoid any IPv4 traffic, remove Avamar from DPC, and then re-add Avamar.
310471	MCS running <code>syncDisplayNameWithVm</code>	MCS runs <code>syncDisplayNameWithVmware</code> if the <code>Rename VM</code> event name contains <code>^vmfs/</code>	N/A



**Table 5. Avamar server known issues (continued)**

Issue ID	Subject/Functional area	Description	Workaround/Resolution
	ware when Rename VM event name contains .vmx prefix.	volumes/*.vmx prefix. This issue typically takes a day to correct itself automatically with the next vCenter synchronization.	
311781	Jetty component on Avamar server and proxy node requires upgrade.	The Jetty component on the Avamar server and proxy node is not at the minimum recommended version.	Upgrade the Jetty component to a minimum of version 9.4.16.
314532	Command output indicates that zzdpn.service failed.	<p>The output of the <code>systemctl status zzdpn.service</code> command indicates that the <code>zzdpn.service</code> failed, even if all DPN services such as GSAN, MCS, and avinstaller are running normally. This error can be ignored, as there is no negative impact to the functionality of the currently running server.</p> <p><b>i NOTE:</b> Operating system-based shutdowns of the Avamar server can result in data loss. The section "Powering off or restarting the server" of the <i>Avamar Administration Guide</i> provides more information about operating system shutdown and reboot best practices.</p>	N/A
317003 esc 36763	urgent restore fails with error Failed to retrieve backup list from account xxx (error code 18 MSG_ERR_NOT_PRESENT)	Urgent restore fails with an error when the SSD is empty.	If the SSD is empty, using <code>avmaint stripestate</code> to bring the stripe online sets it right, and the stripe is rebuilt because it is missing from the disk.
317657	hwfaultd - add check for file system free space approaching 100% full.	When the file system is full, an undefined behavior is observed on ADS.	N/A
318619	Updating gen4t-sys zip to include latest ipmiutil-emc rpm	In gen4t-sys-2.3, which is the payload included with Avamar 19.3.0-122, it is still bundling the older ipmiutil-emc-2.7.9-8.x86_64.rpm. The required fix must bundle ipmiutil-emc-2.7.9-11.x86_64.rpm with a new gen4t-sys-2.4.zip, and update the workflows to include the gen4t-sys-2.4.zip payload.	N/A
319081	AWS m5: get kernel error EDAC skx: Cannot get tolm/tohm every boot time.	Kernel error is observed during the boot time of an AWS m5 instance. It is an indicator that the VM Host implements the <i>SkyLake</i> platform incompletely; the <code>tohm</code> missing message is printed when the operating system tries to decode the EDAC information, and fails to access the required I/O registers. The right way is to implement those registers in the VM Host emulation.	N/A
319461 esc 37431	WC - Win FS Restore - SR<16968788> - Not all permissions are restored when using --restore-acls-only flag.	To convert the xflag into an official flag, a new procedure in flag handling that modifies many APIs must be included.	N/A
320300	ADS4T-SLES11-SP4-64-0001.02.iso and Gen4T, eth0 (shared port) sometimes autonegotiates to 100 Mbps	After kickstart with SLES 12 SP5 v8 ISO, the eth0 interface runs at 100 Mbps on some gen4t nodes, which are not as expected. If the same node is kick started with SLES 11 SP3 1.64, the eth0 interface runs at 1000 Mbps. These nodes	Run <code>ethtool -s</code> to reset the advertised link speed to 1000 Mbps.

**Table 5. Avamar server known issues (continued)**

Issue ID	Subject/Functional area	Description	Workaround/Resolution
		only run 1000 Mbps with SLES 11 SP3 and run 100 Mbps with SLES 11 SP4, SLES 12 SP4, or SLES 12 SP5.	
320741 esc 37619	When VM backup jobs are configured to connect to Data Domain, the proxyDirectives section of the work order is not created.	VM backup job work orders are not created correctly if the backup is to a specific Data Domain in that dedicate customer environment. This is because of the incorrect database operations in that environment, which caused them to have duplicated entries in MCDB.	Remove duplicated entries in MCDB.
321131	Avamar upgrade that is failed at Install Gen4T system tools (95 of 170)	The root cause of failure of the Avamar Upgrade workflow is claimed to be an underlying system pathology that is particular to <i>a4t84d8.datadomain.com</i> . In the case of <i>a4t84d8.datadomain.com</i> , the get-platform-logs command appeared to be unresponsive without completing, which is a strong indication that the BMC on <i>a4t84d8.datadomain.com</i> is in a bad state. If the BMC remains in a bad state, then it might be necessary to do a power-drain procedure, which involves shutting down the node as gracefully as it allows, and then pulling utility power - either using remote power control or by physically pulling the power cables - waiting a minute or so, and then reconnecting power and restarting the node.	N/A
321158	When FIPS is on, every time is boots, there are dracut-pre-trigger modprobe FATAL Model not found messages on the console.	SUSE is investigating this issue. The fatal errors reported seem to be safe to ignore.	N/A
321198	AdaptecEventMonitorService.service incorrectly reported as inactive.	On ADS Gen4T with SLES 12 SP5, <code>systemctl status AdaptecEventMonitorService.service</code> (seen as EventMonitor in 'ps' listings) incorrectly shows the status as <b>inactive</b> , even though the service is up.	N/A
322055	Serviceability report is unresponsive for 1 hour on the multinode Avamar.	Serviceability report becomes unresponsive for an hour because <code>/usr/local/avamar/bin/rptSiteInventory.pl</code> is unresponsive. This issue is observed when the SUDO is not working on the data node.	N/A
324711	Hyper-V-2012 kernel: hv_vmbus: probe failed for device 2450ee40-33bf-4fbd-892e-9fb06e9214cf (-19)	Hyper-V-2012 kernel: hv_vmbus: probe failed for device 2450ee40-33bf-4fbd-892e-9fb06e9214cf (-19). It has a dependency on SuSE.	N/A
325343	Integration Data Protection Appliance 2.6.0: MC is unable to log in to gsan after password change.	AV change password workflow causes the run gsan command of MC to fail after rollback.	Perform the following: <ol style="list-style-type: none"> <li>1. After AV change the password, perform mc flush by using the command <code>mcserver.sh -- flush</code>.</li> <li>2. Create a gsan checkpoint by using the command <code>mccli checkpoint create --</code></li> </ol>

**Table 5. Avamar server known issues (continued)**

Issue ID	Subject/Functional area	Description	Workaround/Resolution
			override_maintenance_scheduler.
325781	AWS: build 19.4.0.77 kernel error: Cannot get hvm parameter CONSOLE_EVTCHN	Kernel error is observed during the boot time of an AWS instance: Cannot get hvm parameter CONSOLE_EVTCHN	N/A

## Avamar Virtual Edition known issues

There are no known issues with Avamar Virtual Edition (AVE) in this release.

## Avamar Web Client (AUI) known issues

The following table lists the AUI known issues in this release:

**Table 6. Avamar Web Client(AUI) known issues**

Issue ID	Subject/Functional area	Description	Workaround/Resolution
326662 esc 38896	Redirected restore from Windows server to Linux fails in 18.2 with path not found in backup error.	Redirected restore from Windows server to Linux fails when accessed from AUI, with path not found in backup error.	Perform the following steps: 1. Restore Windows backup to Windows server. 2. Restore all files (from Windows backup to Linux server) other than a single file.

## Avamar Orchestra known issues

The following table lists the Avamar Orchestra known issues in this release:

**Table 7. Avamar Orchestra known issues**

Issue ID	Subject/Functional area	Description	Workaround/Resolution
307990	Original task records are removed if the Orchestra REST API service is restarted.	Since there is no design for persistence of the internal tasks in the Orchestra REST API, the original task records are removed upon restart of the REST API service.	N/A

## Avamar Administrator known issues

The following table lists the Avamar Administrator known issues in this release:

**Table 8. Avamar Administrator known issues**

Issue ID	Subject/Functional area	Description	Workaround/Resolution
52801	Progress Bytes column in the Activity Monitor displays different values from one Level 0 backup to the next	The value that appears in the <b>Progress Bytes</b> column in the Activity Monitor for backups with the Windows File System plug-in is different from one Level 0 backup to the next for an unchanged backup set. The issue is a display issue only and does not affect the validity of the backup itself.	N/A

**Table 8. Avamar Administrator known issues (continued)**

Issue ID	Subject/Functional area	Description	Workaround/Resolution
263268	Storage utilization capacity of Avamar server node reporting inaccurately	The storage utilization capacity of the Avamar server node that you displayed in the Avamar Administrator is approximate and not an exact value, and has no impact capacity for additional backups.	N/A
325077	Integration Data Protection Appliance 2.6.0: Avamar restarts the agents when changing the AV password.	Avamar restarts the agents when changing the appliance password. Due to this, all active backup jobs must be stopped to change the password.	N/A
326491	Capacity Report.xml incorrectly reports if the system is an AVE.	According to Avalanche data, the AVE flag in Capacity Report.xml is sometimes incorrect. The ADS is wrongly marked to the AVE in the Capacity Report.xml.	N/A
326661 esc 38896	Redirected restore from Windows server to Linux fails in 18.2 with path not found in backup error.	Redirected restore from Windows server to Linux fails in Avamar Administrator.	N/A

## Avamar Client Manager known issues

There are no known issues with Avamar Client Manager in this release.

## Avamar Config Checker known issues

There are no known issues with Avamar Config Checker in this release.

## Avamar Desktop/Laptop known issues

The following table lists the Avamar Desktop/Laptop known issues in this release:

**Table 9. Avamar Desktop/Laptop known issues**

Issue ID	Subject/Functional area	Description	Workaround/Resolution
296558 esc 31191	Avamar does not support NIS authentication with Avamar Desktop/Laptop	This release of Avamar Desktop/Laptop no longer supports users with NIS login feature.	NA

## File level restore client known issues

The following table lists the file level restore client known issues in this release:

**Table 10. File level restore client known issues**

Issue ID	Subject/Functional area	Description	Workaround/Resolution
280373	Issue when browsing a large number of files with Internet Explorer.	When browsing a folder with a large number of files (more than 40,000), Internet Explorer may take more than 2 minutes to complete loading the page, and is not responsive during the loading process. The interim solution to this problem is to use another browser, such as Chrome or FireFox.	N/A
304444	Files are not cleaned up on the target device when work order	When a workorder failure occurs during a file level restore on Linux due to insufficient space	N/A

**Table 10. File level restore client known issues (continued)**

Issue ID	Subject/Functional area	Description	Workaround/Resolution
	failure occurs during file level restore on Linux.	on the target device, the partially copied files do not get cleaned up from the target device, which can result in disk space issues. For example, if restoring 5 GB of files and the target device has only 2 GB of free space, the file level restore fails when the device capacity is reached, but the 2 GB of already copied files remain on the target device.	
321697 esc 37736	FLR fails when esxi has configured multiple network interfaces but the hostname connection is unreachable.	FLR using esxi hostname fallback method fails the whole FLR process even if there is an optimal network route. This issue is observed when a proxy connects to ESXi host and hostname connection has an error. FLR fails because it does not support selecting optimal network from the route table.	N/A
332141	If the target Linux virtual machine contains a Btrfs file system with huge file system metadata, FLR operations can either fail or be slow.	During an Avamar FLR browse or mount operation, a Linux process to change the file system UUID starts on the Avamar proxy host before the file system is mounted.  With a Linux 4 kernel, the Btrfs UUID change process requires all metadata blocks to be rewritten. This process requires a lot of time, and I/O operations. The FLR browse operation works with a "read-only" copy of the backup. The metadata rewrite operation stores the write changes in a temporary file system space on the Avamar proxy host. If the temporary file system space is full or almost full, the FLR operation can fail or be slow.	Perform any of the following workarounds on the Avamar proxy host: <ul style="list-style-type: none"> <li>• Add extra disk space.</li> <li>• Change the file system.</li> <li>• Stop deduplication and other file system features that result in huge metadata.</li> </ul>

## Restore operations fail when deselecting a few files from a folder containing 20,000 files

To work around this issue, complete the following:

1. Use Apache Tomcat to enable Port 8543 which has an unlimited post size. Port 443 has a post size limit and causes restore operations to fail from folders with 20,000 or more files.
2. Start the **Data Protection Backup and Recovery File-Level Restore UI**.
3. Browse to **https://VMware\_Backup\_Appliance\_Host:8543/flr**.
4. Select the files that you are required to restore. Ensure that all the files in the folder are not selected.

## Avamar Web Restore known issues

The following table lists the Avamar Web Restore known issues in this release:

**Table 11. Avamar Web Restore known issues**

Issue ID	Subject/Functional area	Description	Workaround/Resolution
225311	The windows explorer extract does not display restored files.	After restoring multiple files with Web Restore in Microsoft Windows, extracting the compressed files with Windows Explorer does not display the restored files. Install and use the WinZip application to extract and view the files.	N/A

**Table 11. Avamar Web Restore known issues (continued)**

Issue ID	Subject/Functional area	Description	Workaround/Resolution
-	Unable to log in using LDAP in Web Restore with "user-login-module=avamar"	If "user-login-module=avamar" is set in the <code>ldap.properties</code> file on the Avamar server, log in to the Web Restore page using LDAP fails with the message, <code>Error initializing list of backups.</code>	N/A

## Data Domain system integration known issues

The following table lists the Data Domain system integration known issues in this release:

**Table 12. Data Domain system integration known issues**

Issue ID	Subject/Functional area	Description	Workaround/Resolution
51085	New Bytes % displays 0% until backup is complete.	When performing file system backups to a Data Domain system, the <b>New Bytes %</b> field displays 0% until the backup completes.	N/A
53567	<code>hfscheck</code> fails after clients are removed from the <code>/REPLICATE</code> domain and then re-replicated.	When you remove clients from the <code>/REPLICATE</code> domain and the client backups are on a Data Domain system, the garbage collection process removes the replicated backup files from the Data Domain system that is the replication destination. If the client is, then replicated to the Data Domain system again, subsequent <code>hfschecks</code> fail with a <code>MSG_ERR_DDR_ERROR</code> error.	N/A
175640	Avamar cloud tiering does not support Data Domain Hardware HA in DDOS 6.0.	Because of Data Domain issue 175640, the Avamar cloud tiering solution does not support Data Domain Hardware HA in DDOS 6.0. A patch is available from Data Domain to resolve this issue.	N/A
202755	Avamar backups exceeding 10 hours require minimum DDOS version 6.1.1.5-581137.	Any type of Avamar backup to Data Domain that exceeds 10 hours fails if the DDOS version is earlier than 6.1.1.5-581137. Ensure that all Data Domain systems are updated to this version at a minimum.	N/A
287264	Changing the Data Domain system from FQDN to IP results in an error.	When you configure a Data Domain system using the FQDN of the Avamar server, and then update the system to use the IP address instead, the update fails with an error indicating "Failed to connect to Data Domain system." Dell Knowledge Base article 503612 available on the <a href="#">Support</a> page provides more information.	N/A
288864	Avamar does not display the cloud unit name for a backup that is stored on the cloud tier.	If a backup is stored on the cloud tier, the Avamar UI displays <b>Cloud</b> as the storage location rather than the exact name of the cloud unit.	N/A
297904	Replication of Data Domain backups to the target device does not occur immediately when the Avamar client is deleted from the target device.	When you delete the Avamar client from the replication target device in the <b>Avamar Management Console UI</b> , the replicated Data Domain backups on the device are set to "expired." As a result, if you initiate another replication before garbage collection has completed on the target server, the Data Domain backups are not immediately replicated to the target device.	N/A

**Table 12. Data Domain system integration known issues (continued)**

Issue ID	Subject/Functional area	Description	Workaround/Resolution
		If you want to replicate the backups immediately, manually launch garbage collection on the target server, and then restart the replication.	
300657	Trigger group backup takes up to 3 minutes in Cloud Disaster Recovery Advanced Mode.	With Data Domain Cloud Disaster Recovery (DD Cloud DR) enabled and operating in Advanced Mode, interactions between DD Cloud DR and the Avamar server cause group backups to start approximately 3 minutes after you trigger the backup.	N/A
309261	A dual-stack Data Domain system cannot be added when the IPv4 address is inaccessible.	You cannot add a Data Domain system if an inaccessible IPv4 address that resolves to the Data Domain FQDN exists.	Remove the inaccessible IPv4 address in the DNS server, or modify the IPv4 address to a correct address so that a successful connection can be established.
309551	Unable to add Data Domain in a pure IPv6 environment.	In a pure IPv6 environment, if dual stack (IPv4 and IPv6) records exist on the Domain Name Server (DNS), Avamar cannot add the Data Domain system.	Remove the IPv4 entry from the DNS.

## All backup clients and plug-ins known issues

The following table lists all backup clients and plug-ins known issues in this release:

**Table 13. All backup clients and plug-ins known issues**

Issue ID	Subject/Functional area	Description	Workaround/Resolution
32873	Special ACLs are not supported.	The <code>avtar</code> process does not support backup or restore of special UNIX and Linux ACLs such as <code>setuid</code> and <code>setgid</code> bits, or mandatory file lock bits in newer versions of Linux.	N/A
52496	Cluster Configuration Tool fails to activate virtual cluster clients in dual-stack environments.	In a dual stack environment, when the IPv6 address of the Avamar server is used during configuration with the Avamar Cluster Configuration Tool, the Cluster Configuration Tool fails to correctly activate virtual cluster clients.  The interim solution to this problem is to use the Cluster Configuration Tool to create the cluster client, but clear the <b>Bring the cluster client online and activate it with the Avamar server</b> checkbox. Then manually create the virtual cluster client and with Avamar Administrator, and in <b>Policy Management</b> , edit the client and select the <b>Activated</b> checkbox in the <b>Edit Client</b> dialog box.	N/A
56606	Level 1 backup to Data Domain with over 16 critical disks may default to level 0.	After a level 0 backup has been performed for a client with more than 16 critical disks, cache file information for one or more of the disks may no longer be available. The subsequent level 1 backups are also performed as level 0.	N/A
297679	Manage Dataset for Source Data option has discrepancies for MC AUI.	When you create a dataset, under <b>Source Data</b> the <b>File/Folder Path</b> can only be added manually.	N/A
302911	Backup is not supported for SharePoint farms that are	Avamar requires a Windows cluster to function as designed. Avamar does not support configurations on clusterless architectures such as SQL clusterless AAG.	N/A

**Table 13. All backup clients and plug-ins known issues (continued)**

Issue ID	Subject/Functional area	Description	Workaround/Resolution
	configured with SQL clusterless AAG.		

## AIX, HP-UX, Linux, CentOS, and Solaris client known issues

The following table lists the AIX, HP-UX, Linux, CentOS, and Solaris client known issues in this release:

**Table 14. AIX, HP-UX, Linux, CentOS, and Solaris client known issues**

Issue ID	Subject/Functional area	Description	Workaround/Resolution
338194	Ownership of the files that the root user owns would be changed to the non-root user in the new location, while restoring to a different destination.	This action is as per the Linux Filesystem design.	N/A
26077	Push upgrade on Linux fails for nondefault installation location.	Using Avamar upgrade to push an Avamar client upgrade to a Red Hat Enterprise Linux or SuSE Linux Enterprise Server client fails when the Avamar client software is installed in a nondefault location. The use of the <code>rpm</code> option <code>--relocate</code> to install the Avamar client in a nondefault location causes subsequent push upgrades to fail.	N/A
249425	Unable to configure Linux Fast Incremental at runlevel 5 in SUSE12.	Linux Fast Incremental cannot be configured on SUSE 12 file system that is protected at runlevel 5. The interim solution to this problem is to configure the file systems to be protected in run level 3.	N/A
307231	Limitations to <code>avagent</code> services on SLES 12 SP3 or later.	The following limitations apply to the <code>avagent</code> service for Avamar on SuSE Enterprise Linux (SLES) version 12 SP3 or later: <ul style="list-style-type: none"> <li>You can only perform a manual stop and restart the <code>avagent</code> service after running <code>avregister</code>.</li> <li>The <code>avagent</code> service does not start automatically after a system restart. A manual restart of <code>avagent</code> is required.</li> </ul>	N/A
312367, 312368	SLES version 11 still appears in some package names.	Several package names in Avamar 19.2, such as <code>AvamarBundle</code> and <code>avinstaller-bootstrap</code> , still indicate SLES version 11 in the package name.	N/A
322219	The server is unable to detect plug-ins and backup, or the restore jobs that are waiting for the client.	The following issues were observed with Oracle, Sybase, DB2, SAP, and Lotus plug-ins for SLES12 SP4 and SLES 15/15 SP1 platforms: <ul style="list-style-type: none"> <li>Until you manually restart the <code>avagent</code> service, the server is unable to detect the plug-ins.</li> <li>The backup/restore jobs are waiting for the client until you manually restart the <code>avagent</code> service.</li> </ul>	Manually restart the <code>avagent</code> service.



## Microsoft Exchange VSS plug-in known issues

The following table lists the Microsoft Exchange VSS plug-in known issues in this release:

**Table 15. Microsoft Exchange VSS plug-in known issues**

Issue ID	Subject/Functional area	Description	Workaround/Resolution
	Data Domain token authentication issue with clients earlier than Avamar release 7.5	Avamar release 7.5 introduced Data Domain token authentication for the Microsoft application plug-ins. Data Domain token-based authentication is not supported for clients before release 7.5. The interim solution to this problem is to upgrade the clients to release 7.5, or to disable token-based authentication on the Avamar server.	N/A
54465	Restore of an incremental backup fails after restoring a full backup.	If you restore a full backup of an Exchange database and then you restore a subsequent incremental backup of the database, the restore fails.	Rerun the restore and use the <b>Move logs path</b> plug-in option to move the existing log files to a different directory.

## Microsoft Hyper-V VSS plug-in known issues

The following table lists the Microsoft Hyper-V VSS plug-in known issues in this release:

**Table 16. Microsoft Hyper-V VSS plug-in known issues**

Issue ID	Subject/Functional area	Description	Workaround/Resolution
	Performing GLR operation using Azure stack 22H2	The Granular Level Recovery (GLR) is not supported with Azure Stack HCI 22H2.	N/A
338344	Hyper-V Plug-in with Azure stack HCI 21H2 may encounter issues during GLR restore operation.	While performing restore operation on Hyper-V Plug-in with Azure HCI stack 21H2, the Hyper-V GLR restore may face some issues.	N/A
	Data Domain token authentication issue with clients earlier than Avamar release 7.5	Avamar release 7.5 introduced Data Domain token authentication for the Microsoft application plug-ins. Data Domain token-based authentication is not supported for clients before release 7.5. The interim solution to this problem is to upgrade the clients to release 7.5, or to disable token-based authentication on the Avamar server.	N/A
274173	Command-line interface restores from backups on Cloud fail for Microsoft application plug-ins.	Restore operations from the command-line interface do not work for Microsoft application plug-ins (SQL, SharePoint, Exchange, Hyper-V) when the backup resides in the Cloud.  For these restore operations, use the Avamar Management Console's <b>Avamar Administrator</b> window.	N/A
290914	The logfile option cannot be used for Hyper-V, SharePoint, and Exchange backups to specify an alternate path for log file generation.	When performing backups for Microsoft application plug-ins including Hyper-V, SharePoint, and Exchange, you cannot use the <code>logfile</code> option to specify an alternate file path location for the generated log files. Logs can only be generated in the default path <code>C:\Program Files\avs\var\</code> .	N/A
313896	[Windows 2019]For SMB VMs RCT Incremental backup fails for VMs	Whenever VMs are hosted on secondary nodes or remote nodes (passive nodes) other than the	N/A

**Table 16. Microsoft Hyper-V VSS plug-in known issues (continued)**

Issue ID	Subject/Functional area	Description	Workaround/Resolution
	hosted on remote nodes(passive nodes).	primary node, the incremental backups fail with "unable to get the RCT extents" error.	
322762	Avamar Config checker is unable to get the integration services version for Hyper-V VM in the Hyper-V 2016 or 2019 environment.	Avamar Config Checker fails to get the version of Integration Services for VMs hosted on Hyper-V 2016 or 2019 nodes.	N/A
323821	[Windows 2019]AV-Hyper-V VSS Synthetic full restores fail with an error:Hyper-V VSS Writer failed in Post-Restore event on Windows 2019 S2D and on Windows 2019	VSS synthetic full original location restores, and redirected-restores fail with error: Hyper-V VSS Writer failed in Post-Restore event on Windows 2019 S2D and on Windows 2019. For Windows 2019, the RCT workflow is recommended.	N/A
324145	[Windows 2019] AV-Hyper-V VSS redirected restores fail with an error:Hyper-V VSS Writer failed in Post-Restore event on Windows 2019 S2D and on Windows 2019	VSS redirected restores fail with error: Hyper-V VSS Writer failed in Post-Restore event on Windows 2019 S2D and on Windows 2019. For Windows 2019, the RCT workflow is recommended.	N/A

## Microsoft SharePoint VSS plug-in known issues

The following table lists the Microsoft SharePoint VSS plug-in known issues in this release:

**Table 17. Microsoft SharePoint VSS plug-in known issues**

Issue ID	Subject/Functional area	Description	Workaround/Resolution
	Data Domain token authentication issue with clients earlier than Avamar release 7.5	Avamar release 7.5 introduced Data Domain token authentication for the Microsoft application plug-ins. Data Domain token-based authentication is not supported for clients before release 7.5. The interim solution to this problem is to upgrade the clients to release 7.5, or to disable token-based authentication on the Avamar server.	N/A
54465	Restore of an incremental backup fails after restoring a full backup.	If you restore a full backup of an Exchange database and then you restore a subsequent incremental backup of the database, the restore fails.	Rerun the restore and use the <b>Move logs path</b> plug-in option to move the existing log files to a different directory.
246462	Granular Level Recovery on SharePoint 2007 with Windows 2008 R2 fails when the most recent Windows update is not installed.	SharePoint GLR may fail with the following error: Invalid mount letter, most likely caused by AvFS mount failure.	Ensure that the latest updates for Windows 2008 R2 have been installed.

## Microsoft SQL Server plug-in known issues

The following table lists the Microsoft SQL Server plug-in known issues in this release:

**Table 18. Microsoft SQL Server plug-in known issues**

Issue ID	Subject/Functional area	Description	Workaround/Resolution
337342	TLR Mount failure error	When TLR is performed on Windows Server 2022, a user might experience TLR Mount failure with 'mount_media throw ECBFS error'.	Add the <code>--storage-type=stDisk,--largeprefetch=0</code> and <code>--smallprefetch=0</code> flags in <code>axionfs.cmd</code> file and save the file in the AV var folder to stop the mount failure.
-	Redirected restores fail when the location is set in the Restore Options dialog box.	Redirected restore using the <b>Restore to different SQL server instance or location</b> option fails when the location is set using the <b>Set Destination</b> field in <b>Restore Options</b> dialog box. To work around this issue, set the path on the <b>Restore Command Line</b> options page.	N/A
	Data Domain token authentication issue with clients earlier than Avamar release 7.5	Avamar release 7.5 introduced Data Domain token authentication for the Microsoft application plug-ins. Data Domain token-based authentication is not supported for clients before release 7.5. The interim solution to this problem is to upgrade the clients to release 7.5, or to disable token-based authentication on the Avamar server.	N/A
49416	Restore of differential backup after database is removed from availability group may fail.	After a database is removed from an availability group, restores from differential backups of the database might fail.	N/A
54465	Restore of an incremental backup fails after restoring a full backup.	If you restore a full backup of a SQL database and then you restore a subsequent incremental backup of the database, the restore fails.	Rerun the restore and use the <b>Move logs path</b> plug-in option to move the existing log files to a different directory.

## SQL AAG configuration

In SQL AAG configuration, incremental backups on a secondary node may get promoted to full if the SQL server takes time to update LSN inside msdb during previous incremental backup on secondary.

## Microsoft Windows client known issues

The following table lists the Microsoft Windows client known issues in this release:

**Table 19. Microsoft Windows client known issues**

Issue ID	Subject/Functional area	Description	Workaround/Resolution
52801	File size discrepancy for NTFS backups	For Windows NTFS file system backups, the displayed file size of an L0 backup is different than the size displayed for subsequent backups. This problem is a statistical error that is displayed in both the Avamar Administrator and log files, and does not reflect any actual difference between the size of the files in the backups.	N/A
273212	Cluster Shared Volume that is not a part of any role cannot be backed up.	If a Cluster Shared Volume (CSV) is not part of any role, the Avamar system cannot back up the volume. It is not available to be selected in the Avamar Administrator under Windows Cluster File server nor under Windows File System.	N/A
273991	Issue with restore of a Windows 2016 volume that does not support short names	Because of an issue with Windows 2016, during restore of a Windows 2016 volume that does not support short (8.3) names, folders, and files are restored using the short name and no warning is specified.	N/A

## NDMP accelerator node known issues

The following table lists the NDMP accelerator node known issues in this release:

**Table 20. NDMP accelerator node known issues**

Issue ID	Subject/Functional area	Description	Workaround/Resolution
-	Push upgrade to Avamar release 7.3 Service Pack 1 or newer is not supported.	Push upgrade of the NDMP accelerator node from Avamar release 7.3 or earlier to Avamar release 7.3 Service Pack 1 or newer is not supported.	Perform a manual upgrade of the NDMP accelerator node.
60389	Capacity issues occur when Isilon fails to delete snapshots for incremental backups.	When you enable snapshot-based incremental backups for one or more directories on an Isilon system, OneFS does not delete the snapshots after incremental backups occur. Snapshot-based incremental backups are also known as the Faster Incrementals feature. The accumulation of snapshots can result in capacity issues on the Isilon system. This issue is known in OneFS that is fixed in OneFS release 7.1.1.3 or higher and 7.2.0.2 and higher.	Upgrade OneFS to a release that contains the fix, or perform the steps in the <i>Dell Isilon OneFS Backup and Recovery Guide</i> to view and delete snapshots for snapshot-based incremental backups.

## Oracle database plug-in known issues

The following table lists the Oracle database plug-in known issues in this release:

**Table 21. Oracle database plug-in known issues**

Issue ID	Subject/Functional area	Description	Workaround/Resolution
48182	RMAN CLI backups with Oracle RAC configuration do not reflect the scan	RMAN CLI backups with Oracle RAC configuration do not reflect the scan name in the Activity window. The interim solution for this problem is to copy \$ORACLE_RAC_VAR/	N/A

**Table 21. Oracle database plug-in known issues (continued)**

Issue ID	Subject/Functional area	Description	Workaround/Resolution
	name in the Activity window.	<code>avoracle.cmd</code> to <code>\$ORACLE_RAC_VAR/clientlogs/avoracle.cmd</code> .	
273929	Best practices for Oracle and Lotus plug-ins to avoid issues with incremental backup when using a cloud tier	<p>When a cloud tiering policy is configured for Avamar plug-ins for Oracle and Lotus, an earlier Full/L0 backup that is performed through the plug-in may already have been moved to the cloud tier. If this problem is the case, subsequent incremental/L1 backups do not complete, because no parent full/L0 backup is found on the active tier.</p> <p>For the Oracle plug-in, if this issue is encountered, the following error message is written to the plug-in log and the incremental backup fails: An incremental backup was requested but there is no previous full backup. Please perform a full backup before any subsequent full backups.</p> <p>For the Lotus plug-in, the following error message is written to the plug-in log and the incremental backup fails: No Full backup found, Incremental backups cannot be taken without a full backup</p>	<p>The best practice to avoid this issue is to select a Full/L0 backup interval that is smaller than the age threshold configured for moving backups to cloud tier. This step guarantees that the last Full/L0 backup is always available in the Active tier. For Oracle and Lotus plug-ins, after the incremental backup failure, you can either recall the last Full/L0 backup from the cloud tier, or perform a new Full/L0 backup instead of the incremental. Then subsequent incremental backups complete successfully.</p>
277013	Data Domain authentication has a problem when Avamar Plug-in for Oracle installation has insufficient rights.	<p>On Windows systems, when the Avamar Plug-in for Oracle does not have sufficient rights to the <code>&lt;install-dir&gt;\avs\etc\.tmp</code> directory, the Data Domain is unable to write its authentication certificate to the directory, and backups fail. Interim solutions to this problem are:</p> <ul style="list-style-type: none"> <li>• To allow full file access to the oracle user, manually change the privilege of the <code>.tmp</code> directory.</li> <li>• Install the Avamar Plug-in for Oracle in a location that the Oracle user has full file access.</li> <li>• Disable user authentication on the Windows host.</li> </ul>	N/A
281689	Known problem in Oracle, DB2, and Sybase plug-in for SnapView failures	<p>When a backup initiated from the Avamar Administrator fails in the late stages of the backup operation, it is possible that the plug-in application considers the backup to be successful. You cannot perform a restore operation on this backup from Avamar Administrator. Restoring such a backup might still be possible by using a command-line restore. This step is documented as a supported operation in the Oracle Plug-in user guide.</p> <p>How to identify the issue:</p> <ol style="list-style-type: none"> <li>1. The database reports the backup as successful, although the Avamar Administrator reports it as failed.</li> <li>2. Failed backup log messages include an error message that is generated during the late stages of the backup.</li> </ol> <p>For the Avamar Plug-in for Oracle, DB2, and Sybase ASE, the failure is logged with the error message Failed to create the snapview. However, the database data has been successfully backed up and is marked as a hidden backup. Restore is available through CLI only. See the plug-in documentation for information about restoring hidden backups.</p>	N/A

**Table 21. Oracle database plug-in known issues (continued)**

Issue ID	Subject/Functional area	Description	Workaround/Resolution
		<p><b>NOTE:</b> Best practice is to monitor all backup failures and ensure that such cases are followed with a successful full backup. This step requires that you create a successful full backup after any failed backup event.</p>	
283392	Running two RMAN backups on the same database results in unexpected results	<p>When two concurrent backup sessions are initiated on the same database by using Oracle RMAN CLI by using a task file (for monitoring through the Avamar Administrator), one of the backups may fail. The following error message displays on the CLI:</p> <pre>RMAN-03009: failure of backup command on c2 channel at 06/06/2017 11:32:25 ORA-19506: failed to create sequential file, name="ORCL_7us64227_1_1", parms="" ORA-27028: skgfgcre: sbtbackup returned error ORA-19511: Error received from media manager layer, error text: (UTF-8) sbtbackup: aborted!!</pre> <p>Concurrent Oracle RMAN backups using a task file on the same database are currently not supported. Instead, run RMAN database backups using a task file, but archive logs or any other backup for the same database without using a task file.</p>	N/A
293174	In Windows, backup might fail if Oracle is installed with the New Windows User and the Avamar plug-in for Oracle software that is installed in the default path.	Ensure that the Avamar Plug-in for Oracle software is installed outside of the default path C:\Program Files\avs.	<p>If the Avamar Plug-in for Oracle software was installed in the default path C:\Program Files\avs, perform either of the following steps to prevent authentication issues which might cause backups to fail:</p> <ul style="list-style-type: none"> <li>Manually change the privilege of C:\Program Files\avs\etc\temp to give the Oracle user full control.</li> <li>Disable the authentication.</li> </ul>

## IBM DB2 plug-in known issues

The following table lists the IBM DB2 plug-in known issues in this release:

**Table 22. IBM DB2 plug-in known issues**

Issue ID	Subject/Functional area	Description	Workaround/Resolution
286466	Known problem in Oracle, DB2, and Sybase plug-in for SnapView failures	When a backup initiated from the Avamar Administrator fails in the late stages of the backup operation, it is possible that	<p><b>NOTE:</b> Best practice is to monitor all backup failures and ensure that such</p>

**Table 22. IBM DB2 plug-in known issues (continued)**

Issue ID	Subject/Functional area	Description	Workaround/Resolution
		<p>the plug-in application considers the backup to be successful. You cannot perform a restore operation on this backup from Avamar Administrator. Restoring such a backup might still be possible by using a command-line restore. This step is documented as a supported operation in the <i>DB2 Plug-in user guide</i>.</p> <p>How to identify the issue:</p> <ol style="list-style-type: none"> <li>1. The database reports the backup as successful, although the Avamar Administrator reports it as failed.</li> <li>2. Failed backup log messages include an error message that is generated during the late stages of the backup.</li> </ol> <p>For the Avamar Plug-in for Oracle, DB2, and Sybase ASE, the failure is logged with the error message <code>Failed to create the snapview</code>. However, the database data has been successfully backed up and is marked as a hidden backup. Restore is available through CLI only. See the plug-in documentation for information about restoring hidden backups.</p>	<p>cases are followed with a successful full backup. This step requires that you create a successful full backup after any failed backup event.</p>
289136	For consecutive Avamar DB2 restores, the second restore within the new connection timeout period might fail.	<p>When two consecutive Avamar DB2 (avdb2) restores are initiated and the second database restore starts before the previous restore is complete, the second database restore within the new connection timeout period might fail, with the following error displayed in the CLI and the DB2 diagnostic log file <code>db2diag</code>:</p> <pre>SQL2062N An error occurred while accessing media "VENDOR".</pre>	<p>As a best practice, do not start the second database restore until the first restore is completed successfully. Also, before issuing the second DB2 database restore command, ensure that there are no avdb2 processes running on the system. If the previous database restore operation is taking longer than expected, ensure that a sufficiently high value has been set for the flag <b>--timeout-new-connection</b>.</p>

## SAP with Oracle plug-in known issues

The following table lists the SAP with Oracle plug-in known issues in this release:

**Table 23. SAP with Oracle plug-in known issues**

Issue ID	Subject/Functional area	Description	Workaround/Resolution
51870	Oracle Optimized Deduplication option is not supported with Data Domain.	When backing up an SAP with Oracle database to a Data Domain system, the Oracle Optimized Deduplication option is not supported.	N/A

## Sybase ASE plug-in known issues

The following table lists the Sybase ASE plug-in known issues in this release:

**Table 24. Sybase ASE plug-in known issues**

Issue ID	Subject/Functional area	Description	Workaround/Resolution
286467	Known problem in Oracle, DB2, and Sybase plug-in for SnapView failures	<p>When a backup initiated from the Avamar Administrator fails in the late stages of the backup operation, it is possible that the plug-in application considers the backup to be successful. You cannot perform a restore operation on this backup from Avamar Administrator. Restoring such a backup, though not possible through the Avamar Administrator, may still be possible by using a command-line restore. This step is documented as a supported operation in the Sybase Plug-in user guides.</p> <p>How to identify the issue:</p> <ol style="list-style-type: none"><li>1. The database reports the backup as successful, although the Avamar Administrator reports it as failed.</li><li>2. Failed backup log messages include an error message that is generated during the late stages of the backup.<ul style="list-style-type: none"><li>• For the Avamar Plug-in for Oracle, DB2, and Sybase ASE, the failure is logged with the error message: Failed to create the snapview. However, the database data has been successfully backed up and is marked as a hidden backup. Restore is available through CLI only. See the plug-in documentation for information about restoring hidden backups.</li><li>• For an incremental backup, the failure is logged with the error message: If a transaction log truncation was performed during an incremental backup of a Sybase database with the data and log on separate devices, the transaction log is now at risk of being lost. Perform an immediate full backup of the impacted database to protect the data. Consult the Avamar Plug-in for Sybase documentation for more information.</li></ul></li></ol>	<p><b>NOTE:</b> Best practice is to monitor all backup failures and ensure that such cases are followed with a successful full backup. This step requires that you create a successful full backup after any failed backup event.</p>



## IBM Lotus Domino plug-in known issues

The following table lists the IBM Lotus Domino plug-in known issues in this release:

**Table 25. IBM Lotus Domino plug-in known issues**

Issue ID	Subject/Functional area	Description	Workaround/Resolution
239003	The server field in the Activity window is blank for the CLI restore operation.	The Server field in the Activity windows is blank for restore operations that are performed on the command line.	N/A
273929	Best practices for Oracle and Lotus plug-ins to avoid issues with incremental backup when using a cloud tier.	<p>When a cloud tiering policy is configured for Avamar plug-ins for Oracle and Lotus, an earlier Full/L0 backup that is performed through the plug-in may already have been moved to the cloud tier. If this problem is the case, subsequent incremental/L1 backups do not complete, because no parent full/L0 backup is found on the active tier.</p> <p>For the Oracle plug-in, if this issue is encountered, the following error message is written to the plug-in log and the incremental backup fails: An incremental backup was requested but there is no previous full backup. Please perform a full backup before any subsequent full backups.</p> <p>For the Lotus plug-in, the following error message is written to the plug-in log and the incremental backup fails: No Full backup found, Incremental backups cannot be taken without a full backup</p>	The best practice to avoid this issue is to select a Full/L0 backup interval that is smaller than the age threshold configured for moving backups to cloud tier. This step guarantees that the last Full/L0 backup is always available in the Active tier. For Oracle and Lotus plugins, after the incremental backup failure, you can either recall the last Full/L0 backup from the cloud tier, or perform a new Full/L0 backup instead of the incremental. Then subsequent incremental backups complete successfully.
305687	Avlotus backups complete successfully but report "[AvlotusMonitorCancel]INTERNALERROR: <0001>assert error."	On the Lotus plug-in for some AIX systems, a backup is displayed as completed with errors, even when the backup is successful and available for recovery, due to an assertion failure that occurs while unlocking a mutex at the end of the backup. This error can be ignored.	N/A
314742	The domino plug-in cannot restore NLO file with the overwrite option selected.	The Avamar Plug-in for Lotus Domino is unable to restore an individual NLO file when the overwrite option is selected due to case-sensitive path comparison for the NLO path.	Ensure that the DAOS folder name in the NLO path is in ALL CAPS.

## Replication known issues

The following table lists the replication known issues in this release:

**Table 26. Replication known issues**

Issue ID	Subject/Functional area	Description	Workaround/Resolution
192169	Incorrect statistics appear for replication of Avamar	When you replicate Avamar backup data from one Data Domain system to another Data Domain system, incorrect statistics appear for:	N/A

**Table 26. Replication known issues (continued)**

Issue ID	Subject/Functional area	Description	Workaround/Resolution
	backup data on a Data Domain system.	<ul style="list-style-type: none"> <li>• The file total in the <code>avtar</code> log file.</li> <li>• The progress bytes in the Activity Monitor in Avamar Administrator.</li> </ul>	
262220	Invalid certificate after upgrading and reconfiguring a replication destination server	<p>Reconfiguring the destination server for replication fails with the following an error message under the following conditions: Could not log in to remote destination. Check credentials and hostname or IP. Authentication failed.</p> <ul style="list-style-type: none"> <li>• After a replication is performed from a source Avamar server to a destination Avamar server that uses certification-based authentication.</li> <li>• Upgrading the destination server to a new version of Avamar.</li> <li>• Deleting the replication configuration.</li> </ul> <p>The interim solution for this problem is to issue the following commands at the source server:</p> <pre>rm -rf /usr/local/avamar/etc/&lt;destination server IP&gt; rm -rf /usr/local/avamar/etc/client/&lt;destination server IP&gt;</pre>	N/A
277208	Check for Remote backups before deletion not working.	During replication, when the <b>Check for Remote backups before deletion</b> option is selected, the server deletes the replication destination record even if remote backups exist on the replication destination system.	N/A
309113	Replication job that is canceled after partial creation or completes with an exception displays as VALID in the AUI.	If a replication job is canceled after being partially created on the destination system, or completes with an exception, the status of the job displays as <b>VALID</b> in the <b>Asset Management</b> window of the <b>AUI</b> , with no warning to indicate that any issue occurred.	N/A
309388	Restore of replicated backups fails when the source and destination Avamar system that is attached to the same Data Domain.	You cannot perform a restore of a replicated backup when the system with the Avamar source backup and the destination system for the restore are attached to the same Data Domain.	N/A
309501	Replication status was failed at Avamar destination, but the replication was successful.	Due to a timeout that occurs when there are 5000 or more clients in a domain, the destination system for a replication displays the replication job as "Failed" even though the job was completed successfully, as indicated on the source.	N/A
309624	Replication fails if both IPV4 and IPV6 records exist in the DNS server for the Avamar destination.	Replication to the Avamar destination in a pure IPv6 environment (where both IPv4 and IPv6 records exist in the DNS server but IPv4 is not configured) fails, with an error message in the Activity logs of <b>Avamar Administrator</b> indicating "Unable to connect to the IPv4 address of the Destination Avamar."	Remove the IPv4 entry from the DNS.

## Avamar Data Migration Enabler (ADMe) known issues

The following table lists the ADMe known issues in this release:

**Table 27. Avamar Data Migration Enabler known issues**

Issue ID	Subject/Functional area	Description	Workaround/Resolution
253574	Staging and tape out of Sybase backups are not supported.	Due to a known limitation with the ADMe software, staging and tape out of backups that are created with the Sybase plug-in is not supported in this release.	N/A

## Upgrade known issues

The following table lists the upgrade known issues in this release:

**Table 28. Upgrade known issues**

Issue ID	Subject/Functional area	Description	Workaround/Resolution
327044	The preinstalled and postinstalled <code>os-rollup survey results.xml</code> must be copied into the data node.	When upgrading from 19.4.0-68 to 19.4.0-114 on Gen4T multiple nodes, rollup-2020-R3-v4 can be installed on both utility nodes and data nodes. But only the utility node has the preinstalled postinstalled <code>os-rollup survey results.xml</code> . All data nodes do not have <code>os-rollup survey results.xml</code> .	N/A

## VMware known issues

The following table lists the VMware known issues in this release:

**Table 29. VMware known issues**

Issue ID	Subject/Functional area	Description	Workaround/Resolution
37029	Updated values are not considered during Proxy Deployment.	When you edit the saved values multiple times in the proxy deployment process, it does not replace the initial saved values with the new values.	To add the new values, use the <b>Create Proxy</b> option instead of the <b>Edit Proxy</b> option.
337008	Proxy recommendation fails to start and throws an internal error in the AUI.	When you install OS rollup 2022-R3-v4 on a new ADS server, the permission of some of the web application directories change, which results in the failure of redeployment of these directories. As a result, the proxy recommendation fails to start and throws an error in the AUI.	See the section "Obtain proxy recommendation" in the <i>Avamar Administration Guide</i> for details on the workaround.
34477	Domain user not supported for file-level restore of virtual machine backup	For non-Windows platforms, you cannot perform file-level restore of a virtual machine backup as a Domain user. The user can be part of the Standard or Administrators group.	N/A
-	Exclude the proxy from the virtual machine backup if performing the backup with other VMware software.	Including the Avamar proxy in a backup consumes a large amount of space. When using other VMware software instead of the Avamar software to perform the virtual machine backup, it is recommended that you exclude the proxy virtual machine from the backup.	N/A
-	Adding vCenter as IPv6 address is not supported, use FQDN instead.	When you register or add a VMware vCenter client to Avamar, ensure that you specify the fully qualified domain	N/A

**Table 29. VMware known issues (continued)**

Issue ID	Subject/Functional area	Description	Workaround/Resolution
-	HotAdd mode does not work with a VSAN disk.	name (FQDN) of the vCenter. Using the IPv6 address is not supported.  Due to a known limitation with VMware, documented in the VDDK 6.0.1 release notes regarding vSAN 6.1, ESXi hosts do not allow HotAdd of a vSAN disk on a proxy virtual machine with datastore types other than vSAN. As a result, in a vSAN 6.1 environment, attempts to HotAdd a VMDK vSAN datastore by a proxy residing outside vSAN fails. If HotAdd mode is wanted, host the proxy on the vSAN datastore.	N/A
248502	Support for validation of VMware image backup in MCCLI is limited.	When you use the <code>mccli backup validate</code> , validation is scheduled but the activity is in a waiting-client state. The <code>--dest-client-name</code> and <code>--dest-client-domain</code> options are not supported when validating a non-/REPLICATE client backup.	N/A
248775	Proxy running on a non-PDL datastore is getting powered off during a PDL of virtual machine datastore.	The virtual machine proxy can get abruptly powered off if the proxy is engaged in a HotAdd backup of a VMCP-enabled virtual machine, in the event of a permanent device loss of the virtual machine datastore. This problem might occur due to HA attempting to restart the proxy virtual machine, as it would have mounted the VMDK of the virtual machine.  The interim solution to this problem is to ensure that the next schedule starts correctly, which manually removes all the hotadd disks from the Avamar proxy, and power it back on. A snapshot consolidation may also be required for the virtual machine.	N/A
263450	File-level restore not supported for GPT/EFI drives on Windows 2012 when a third-party disk tool edits the drive.	Avamar does not support the use of GPT/EFI drives on Windows 2012 for file-level restore operations when a disk tool from a third-party software vendor edits the drive. Before mounting the drive for file-level restore, verify that all the disks on the virtual machine have valid/supported partitions.	N/A
278280	Instant Access that is not supported with cloud tiering.	Instant Access restores are not supported for data that is migrated to the cloud using the cloud tiering feature.	N/A
282640	Restoring a remote backup fails when the restore is to a specific ESXi that is different from the original ESXi server.	Restoring a remote backup fails when the restore is to a specific ESXi that is different from the original ESXi server. The interim solutions to this problem are: <ul style="list-style-type: none"> <li>• If a local backup exists, restore the local backup to the specific ESXi.</li> <li>• If a local backup does not exist, and the original ESXi is running, restore the remote backup to the original ESXi and then restore the remote backup to the specific ESXi.</li> </ul> Use the <code>avrepl</code> command to replicate the remote backup to the source Avamar when the following occurs: <ul style="list-style-type: none"> <li>• A local backup does not exist.</li> <li>• The original ESXi is not running.</li> </ul> Restore the local backup to the specific ESXi: <pre>avrepl --[replscript]restore=true --operation=replicate -- [replscript]dstaddr=SRC_ADDR --[replscript]dstid=repluser</pre>	N/A

**Table 29. VMware known issues (continued)**

Issue ID	Subject/Functional area	Description	Workaround/ Resolution
		<pre>--dstpassword=Chang3M3Now. --ap=Chang3M3Now. -- [replscript]dpnname=SRC_ADDR --[replscript]dstencrypt=tls / REPLICATE/CLIENTPATH</pre> <p>Where <i>SRC_ADDR</i> is the IP address of the source Avamar server and <i>CLIENTPATH</i> is the client path. If <i>CLIENTPATH</i> is a domain, instead of a path, it moves all the clients' backups under the domain.</p>	
290464 29814	BMR fails.	<p>When performing bare metal recovery (BMR) to a virtual machine with VMware hardware version 11, the following problems might occur:</p> <ul style="list-style-type: none"> <li>• WinPE cannot find a virtual disk.</li> <li>• The restored virtual machine does not boot.</li> </ul>	<p>The following workarounds apply:</p> <ul style="list-style-type: none"> <li>• Restore the system backup to a virtual machine with VMware hardware version 8 or 9.</li> <li>• Ensure that the hardware configuration of the target host is the same as the hardware configuration of the source host.</li> </ul>
291803	When logged in as Local user with an administrator role, Advanced Policy Builder fails to install, upgrade, or register client agents on SQL Virtual machines.	Due to the introduction of User Account Control (UAC) in Microsoft Windows 7 and later versions, when logged in as a Local user with the administrator role, the <b>Advanced Policy Builder</b> fails to install/upgrade/register client agents on SQL virtual machines.	On the guest operating system, turn off <b>Admin Approval Mode</b> in the UAC settings for the admin group.
292446	During a restore, the virtual machine Generation ID might not increment which might cause data loss.	If a virtual machine with the Active Directory role is restored by using the Avamar backup data loss might occur as a result of a USN rollback. In this scenario, the restored virtual machine retains the same virtual GenerationID as the source virtual machine.	<p>Perform the following workaround:</p> <ol style="list-style-type: none"> <li>1. Restore the virtual machine from the backup.</li> <li>2. Do not start the virtual machine.</li> <li>3. Take a snapshot of the virtual machine by using VMware.</li> <li>4. Revert the virtual machine to the snapshot.</li> <li>5. Start the virtual machine.</li> </ol>
293950	Virtual machine client jobs in waiting, failed, or canceled state might not get restarted after fail-over.	After a vCenter high availability fail-over, the <b>Avamar Management Console</b> may not restart the virtual machine client jobs that were in a waiting, failed or canceled state before the fail-over.	If this issue occurs, restart the <b>Avamar Management Console</b> services.
300223	If a rule is not created to exclude proxy VMs when rule-based protection is	PDM registration fails , and the following error message appears if a rule is not created to exclude proxy VMs when rule-based protection is used: <code>Could not register proxy: invalid domain</code>	When using rule-based protection, create a rule to exclude proxy VMs.

**Table 29. VMware known issues (continued)**

Issue ID	Subject/Functional area	Description	Workaround/Resolution
		used, PDM registration fails.	
307561	Image-level virtual machine restore for a large (1400+) number of virtual machines simultaneously is not supported.	Performance issues are observed when performing 1400 or more image-level virtual machine restores simultaneously.	N/A
309541	Limitations to vCenter High Availability	<p>Note the following limitations that are related to support for vCenter High Availability (VCHA):</p> <ul style="list-style-type: none"> <li>• If the proxy is not available after the VCHA event, a restart order gets issues for all failed or restarted jobs, which will not complete because the proxy is not available.</li> <li>• If <b>Hot Add</b> transport mode is used for the virtual disks and the proxy fails, all the associated clients with <b>Hot Add</b> disks in the proxy fail, and a new backup cannot be performed.</li> </ul>	<p>Perform the following workaround.</p> <ol style="list-style-type: none"> <li>1. Bring the proxy back online, and then perform a manual backup with the same proxy. Disks are consolidated, and the backups proceed.</li> <li>2. Manually remove all <b>Hot Add</b> disks from the proxy.</li> </ol>
309934	Jetty service continues to run in proxy virtual machine after stop command.	When you run the <code>service jetty stop</code> command to stop the jetty service in the proxy virtual machine, the back-end process continues to run.	Stop the back-end jetty process manually.
319308	Backup failed in Avamar 19.3 with VMC 1.10.	In Avamar release 19.3, Virtual Machine backup is not supported with VMware VMC 1.10 release.	N/A
319375	Backup failed in Avamar 19.3 with VMC 1.9.	In Avamar release 19.3, Virtual Machine backup is not supported with VMware VMC 1.9 release.	N/A
319482	Virtual Machine image restore to a different existing VM is not supported.	Virtual Machine image restore to a different existing VM is not supported.	N/A
320131	Vddk errors are seen for successful VM Image backup and restore.	Vddk error during VM Image backup and restore "Error while loading feature config file: /etc/vmware/vsphereFeatures/vsphereFeatures.cfg, using default feature state values." This error is treated as warning message from a proxy perspective and is safe to ignore.	N/A

## Supportability package known issues

The following table lists the Avamar supportability package known issues in this release:

**Table 30. Supportability package known issues**

Issue ID	Subject/Functional area	Description	Workaround/Resolution
33892	Unnecessary Upgrade Client Downloads package option	<p>The Upgrade Client Downloads package presents a <b>Show advanced settings</b> option on the installation page <b>skip upgrading client download rpms</b>.</p> <p>If you select the <b>Values</b> check box and click <b>Continue</b>, client downloads are not upgraded on</p>	Do not select <b>Show advanced settings</b> on the installation page.

**Table 30. Supportability package known issues**

Issue ID	Subject/Functional area	Description	Workaround/Resolution
		the system and the package no longer appears in Avamar Installation Manager.	
		If you clear the <b>Values</b> check box and click <b>Continue</b> , the client downloads upgrade works as designed.	

## Avamar plug-in for vSphere Web Client configuration application known issues

There are no known issues with Avamar plug-in for vSphere Web Client configuration application in this release:

## Environment and system requirements

The following sections describe specific environment and system requirements that are associated with this release of Avamar.

### Client, server, and platform compatibility

Updated and detailed client, sever, and platform compatibility information is available in E-LAB Navigator at <https://elabnavigator.dell.com/eln/elhome>.

### Client hardware requirements

Client hardware requirements are listed in each client user guide, such as the *Avamar for Oracle User Guide*, *Avamar for Windows Server User Guide*, or *Avamar for SQL Server User Guide*. A full list of Avamar documentation is available in [Documentation](#).

### Avamar Downloader Service operating system requirements

Beginning with release 7.3, the Avamar Downloader Service is now available on the Avamar utility node or single-server node. The Windows-based legacy Avamar Downloader Service is also supported and is available on the following Windows platforms:

- Windows Server 2019
- Windows Server 2016
- Windows 10
- Windows Server 2012 (64-bit only)
- Windows Server 2008 R2
- Windows 8
- Windows 7 SP1

The *Avamar Administration Guide* provides a list of supported operating systems for the Avamar Downloader Service.

### Data Domain system requirements

Updated, detailed, supported DD OS and DD Boost version information is available in the E-LAB Navigator at <https://elabnavigator.dell.com/eln/elhome>.

# International language support

The following sections provide important information about international language support in Avamar:

## International language support in Windows environments

Supported languages for Windows environments include:

- Arabic
- Bulgarian
- Chinese (Simplified and Traditional)
- Croatian
- Czech
- Danish
- Dutch
- Estonian
- Finnish
- French
- German
- Greek
- Hebrew
- Hungarian
- Italian
- Japanese
- Korean
- Latvian
- Lithuanian
- Norwegian
- Polish
- Portuguese (Brazilian)
- Romanian
- Russian
- Slovak
- Slovenian
- Spanish (Iberian and Latin American)
- Swedish
- Turkish

Table 31. Windows environment international language support

Windows data type	International language support details
Windows files and folders	<p>You can back up and restore individual files and folders with file and folder names in local languages.</p> <p>File and folders names appear in the local language in Avamar Administrator and Avamar Web Restore.</p>
Microsoft Exchange databases	You can back up and restore databases with the database name in supported local languages.
Microsoft Exchange folders and messages	You can back up and restore individual folders and messages with the folder or message name in supported local languages.
Microsoft SQL Server databases	You can back up and restore databases with the database name in supported local languages.

## International language support in UNIX and Linux environments

Supported languages for UNIX and Linux environments include:

- Arabic
- Bulgarian
- Chinese (Simplified and Traditional)
- Croatian
- Czech
- Danish
- Dutch
- Estonian
- Finnish
- French
- German
- Japanese
- Korean
- Latvian
- Lithuanian
- Norwegian
- Polish
- Portuguese (Brazilian)
- Romanian
- Russian
- Slovak
- Slovenian



- Greek
- Hebrew
- Hungarian
- Italian
- Spanish (Iberian and Latin American)
- Swedish
- Turkish

**Table 32. Windows environment international language support**

Encoding	International language support details
EUC-JP	<p>You can back up and recover EUC-JP encoded files and directories with names in the Japanese language on Solaris.</p> <p><b>NOTE:</b> EUC-JP encoded file and directory names do not render correctly in either Avamar Administrator or Avamar Web Restore. This issue does not apply to the client web UI available through Avamar Desktop/Laptop.</p>
UTF	<p>You can back up and restore individual UTF-encoded files and directories with file and directory names in supported local languages.</p> <p>File and directory names appear in the local language in Avamar Administrator and Avamar Web Restore.</p>

## Known limitations of local language support

Consider the following known limitations of local language support:

- Cross-platform redirected restore of files and directories with international character set names is not supported.
- Client machine hostnames must consist entirely of ASCII characters.
- The client software installation path must consist entirely of ASCII characters.
- Policy objects (such as, users, groups, datasets, schedules, retention policies, notification profiles) must consist entirely of ASCII characters.
- Log files do not correctly render non-ASCII characters.
- Error, warning, and informational messages incorrectly render non-ASCII characters, both to the screen and to log files.
- Log files which are based on user-defined names (for example, database names) do not work correctly.
- You cannot use non-ASCII characters in options and flags. If a flag or option takes a file, folder, or identifier (for example, a database name), then that option is only assured to work for ASCII names.
- Sorting is not localized. Sorting is strictly by byte-ordinal value.
- You cannot type local language characters in the Avamar user interface using a keyboard.
- The Avamar Management Console Command Line Interface (MCCLI) and `avtar` support only ASCII arguments on the command line.

## Restore international characters with Avamar Web Restore

The Avamar Web Restore feature restores directories or multiple files in the form of a Zip file. When you unzip the Zip file, file and directory names with international characters might not restore correctly due to inherent limitations in some Zip utilities.

To correctly restore files with international characters by using the Avamar Web Restore feature, use a Zip utility that supports international characters. Examples are:

- Winrar 3.80 or later
- Winzip 12.0 or later
- 7zip 4.65 or later

Do not use Microsoft Windows compressed folders with the Avamar Web Restore feature. These compressed folders do not reliably handle international characters.

## Support for non-UTF8 locales in the Management Console

Avamar includes support for browsing non-UTF8 file systems from the Management Console. The following Java character sets are supported:

Big5	Big5-HKSCS	COMPOUND_TEXT
EUC-JP	EUC-KR	GB18030
GB2312	GBK	IBM-Thai
IBM00858	IBM01140	IBM01141
IBM01142	IBM01143	IBM01144
IBM01145	IBM01146	IBM01147
IBM01148	IBM01149	IBM037
IBM1026	IBM1047	IBM273
IBM277	IBM278	IBM280
IBM284	IBM285	IBM297
IBM420	IBM424	IBM437
IBM500	IBM775	IBM850
IBM852	IBM855	IBM857
IBM860	IBM861	IBM862
IBM863	IBM864	IBM865
IBM866	IBM868	IBM869
IBM870	IBM871	IBM918
ISO-2022-CN	ISO-2022-JP	ISO-2022-JP-2
ISO-2022-KR	ISO-8859-1	ISO-8859-13
ISO-8859-15	ISO-8859-2	ISO-8859-3
ISO-8859-4	ISO-8859-5	ISO-8859-6
ISO-8859-7	ISO-8859-8	ISO-8859-9
JIS_X0201	JIS_X0212-1990	KOI8-R
KOI8-U	Shift_JIS	TIS-620
US-ASCII	UTF-16	UTF-16BE
UTF-16LE	UTF-32	UTF-32BE
UTF-32LE	UTF-8	windows-1250
windows-1251	windows-1252	windows-1253
windows-1254	windows-1255	windows-1256
windows-1257	windows-1258	windows-31j
x-Big5-Solaris	x-euc-jp-linux	x-EUC-TW
x-eucJP-Open	x-IBM1006	x-IBM1025
x-IBM1046	x-IBM1097	x-IBM1098
x-IBM1112	x-IBM1122	x-IBM1123
x-IBM1124	x-IBM1381	x-IBM1383
x-IBM33722	x-IBM737	x-IBM834
x-IBM856	x-IBM874	x-IBM875
x-IBM921	x-IBM922	x-IBM930
x-IBM933	x-IBM935	x-IBM937
x-IBM939	x-IBM942	x-IBM942C
x-IBM943	x-IBM943C	x-IBM948

x-IBM949	x-IBM949C	x-IBM950
x-IBM964	x-IBM970	x-ISCII91
x-ISO-2022-CN-CNS	x-ISO-2022-CN-GB	x-iso-8859-11
x-JIS0208	x-JISAutoDetect	x-Johab
x-MacArabic	x-MacCentralEurope	x-MacCroatian
x-MacCyrillic	x-MacDingbat	x-MacGreek
x-MacHebrew	x-MacIceland	x-MacRoman
x-MacRomania	x-MacSymbol	x-MacThai
x-MacTurkish	x-MacUkraine	x-MS932_0213
x-MS950-HKSCS	x-mswin-936	x-PCK
x-SJIS_0213	x-UTF-16LE-BOM	X-UTF-32BE-BOM
X-UTF-32LE-BOM	x-windows-50220	x-windows-50221
x-windows-874	x-windows-949	x-windows-950
x-windows-iso2022jp		

## Technical notes

This section describes important notes and tips for using Avamar.

### Avamar server technical notes

The following technical notes apply to the Avamar server.

#### Common Vulnerabilities and Exposures (CVE) list

Avamar engineering addresses Common Vulnerabilities and Exposures (CVE) in operating system patch releases (also known as OS Rollup releases). A list of all CVEs addressed is provided in the Security Advisory for each OS Rollup release.

#### Remove test data

Before starting the server or starting a new node for the first time, ensure that all test data is removed from `/data*/` partitions. In particular, if you ran disk tests before startup, you might need to delete directories that are named QA.

#### Do not use the avmgr command

Improper use of the `avmgr` command line utility can destroy all access to data in the Avamar system. Use this command only at the explicit direction of Customer Service.

#### Vulnerability scanning

As part of every Avamar release, the product is scanned for vulnerabilities using at least two common vulnerability assessments tools. This release was scanned with Foundstone and Nessus. Various customers scan the Avamar solution by using tools such as eEye Retina without issue. However, it is possible that the usage of other port/vulnerability scanners might cause disruption to normal operation of the Avamar server. Therefore, it might be necessary to disable scanning of the Avamar server when problems occur.

## Avamar 7.2 and later scalability limits for virtualization support

The scalability limits of each Avamar 7.2 and greater with Data Domain integrated solution are approximately:

- 5000 virtual machine clients
- 180TB provisioned virtual machine storage
- 72 concurrent backup proxy client stream instances (not proxy virtual machines)

These limits are applicable only when the backup data is sent to the Data Domain system and assume that the Data Domain is correctly specified to support the backup, restore, and, if applicable, replication activities. These limits may be impacted if additional client types are backed up to the Avamar/Data Domain solution. These limits may be further limited by the overall performance of the VMware environment, including the performance of the Avamar Virtual Edition server, if applicable.

Customers who plan to operate near these limits should validate their deployments with their account representative.

## VMware image proxies are not available for backups when they are in sleep mode and you restart the MCS

If you stop the MCS and do not restart the MCS within 5 minutes, then VMware image proxies go into a sleep mode for 40 minutes. When you restart the MCS, it might take some time until all proxies reconnect to the MCS and are available for backups. This issue can occur when performing backups after a rollback.

To ensure that all proxies are available, open the `avagent.log` file on each proxy, and ensure that the following messages appear at the bottom of the log:

```
yyyy-mm-dd hh:mm:ss avagent Info <5964>: Requesting work from 10.2.345.678
yyyy-mm-dd hh:mm:ss avagent Info <5264>: Workorder received: sleep
yyyy-mm-dd hh:mm:ss avagent Info <5996>: Sleeping 15 seconds
```

The messages indicate that the proxy can connect to the MCS. The `avagent.log` file is available in the `/usr/local/avamarclient/var` directory.

## AMS replication after an IP address change

If you change the IP address that you use for replication with Avamar and one or more Data Domain systems, then the first replication after the change uses Automated Multistreaming (AMS) replication. Subsequent replications use Virtual Synthetic Replication (VSR).

## Original Bytes are displayed as twice the original size

The **Original Bytes** value appears as twice the original size when you run the Data Domain `filesys show compression` command in the Avamar namespace on the Data Domain system.

## Token based authentication notes

Data Domain version 5.7.1.x or later supports token based authentication. Previous versions fall back to traditional connection. Clients must use a resolvable Fully Qualified Domain Name to use token based authentication.

## Avamar Administrator technical notes

The following technical notes apply to Avamar Administrator.

## Avamar Administrator directory browsing limitation

When browsing a client file system with Avamar Administrator, large numbers of files in the directories can cause Avamar Administrator to run out of memory. Avamar Administrator is configured by default to only retrieve the first 50,000 files in each directory. Change this limitation by editing the `max_browse_entries` settings in `mcserver.xml` and `mcclient.xml`. However, this step could cause unpredictable application behavior.

## Jobs do not appear in the Activity Monitor after server restart

If the administrator server is stopped and restarted, the jobs that started before the administrator server stop do not appear in the Activity Monitor.

## Schedule start times and end times

If a different start time is selected in the schedule, reselect the desired end time.

## Client name change impacts license quota

If a client is renamed, the old name of the client remains for activities reporting data for the client. Avamar treats new activities for the same client as if they were for a new client, leading to double counting the number of bytes protected for licensing purposes. If a client name change is required, consult Dell Customer Service to ensure that the database is correctly updated.

## Additional “cold start” messages from netsnmp

To resolve an issue where SNMP stops responding, Avamar must frequently restart the `netsnmp` agent. The `netsnmp` agent generates a “cold start” message on each restart, in which additional “cold start” messages that are unrelated to actual restart of the Avamar system or incorrect operation of the system appear. However, there are some difficulties to distinguish between a real “cold start” message from the restart of Avamar system and a “cold start” message that is generated as the result of `netsnmp` agent restarts.

## Software conflicts with Black Ice and Timbuktu

The Avamar Administrator software is known to have conflicts with software packages such as Black Ice and Timbuktu.

## Avamar Desktop/Laptop technical notes

The following technical notes apply to Avamar Desktop/Laptop.

### Client-level Avamar accounts cannot log in to Avamar Desktop/Laptop

To provide the same level of security that exists in Avamar Administrator, Avamar Desktop/Laptop blocks Avamar's default client-level accounts. The issue shows that Avamar Desktop/Laptop does not accept the credentials for the following default accounts:

- backuponly
- restoreonly
- backuprestore
- replonly

### Back up System State option not recommended

For datasets with the Windows file system plug-in, do not enable the **Back up System State** option when using Avamar Desktop/Laptop.

### Entourage support requires default installation location

The Avamar Client for Mac OS X supports Microsoft Entourage by using scripts that shut down the Microsoft Database daemon before starting a backup. Restart the database after the backup completes. These scripts do not work when the Avamar Client for Mac OS X is installed in a non-default location. To support clients for Entourage, use the default location when installing the Avamar Client for Mac OS X.

## Viewing logs from the Mac console requires default installation

When the Avamar Client for Mac OS X is installed in a non-default location, work order logs cannot be viewed from the Avamar client console. To view a work order log, open the text editor from the clientlogs folder.

## Default limit for process data segments is too low

On Mac OS X, the default limit for process data segments (6 MB) is lower than the limit of 96 MB that Dell recommends. Any value below 96 MB affects the backup and restore performance.

During installation of the Avamar for Mac OS X Client, the installer looks at the value of this setting. If the value is less than 96 MB, the installer should change to 96 MB. The new value takes effect after the computer restarts.

The installer then launches a restart reminder. To ensure optimal performance, restart the computer as soon as possible after completing the installation.

## Extended drives are visible on some operating systems

On some operating systems, extended or mapped network drives can be seen in the **Restore Location** dialog box. While a restore to the drive may work, depending on permissions and domain settings, it is not supported.


## Avamar Web Restore technical notes

The following technical notes apply to Avamar Web Restore.

### Enabling the full display on the Avamar login screen

Avamar Web Restore displays an empty **Domain** field and an empty **Client** field on the Avamar login screen. This step prevents the display of domain information during a non-domain login. When using Avamar Web Restore only in a secure domain, change the default setting to enable the full display on the screen.

When the full display is enabled, a list of Avamar domains appears in the **Domain** field and a list of clients appears in the **Client** field.

 **NOTE:** This change does not affect the Avamar Web Restore LDAP login screen.

To enable the full display on the Avamar log in screen, perform the following steps:

1. Open a command shell and log in:
  - For a single-node server, log in to the server as root.
  - For a multi-node server, log in to the utility node as root.
2. Switch user to root by typing the following command:

```
su -
```
3. Change the current working directory by typing the following command:

```
cd /usr/local/avamar/etc
```
4. Open the Avamar Desktop/Laptop properties file, `dtlt.properties`, in a plain text editor.
5. Add the `showWRClientList` key with the value of `true`:

```
showWRClientList=true
```

If the key exists, set the value to `true`.
6. Save and close the file.

### Special characters in file name replaced during restore

Restoring a file with special characters in the file name results in replacement of the characters in the restored file name. This step occurs when the `LANG` variable on the Avamar server is set to a locale that does not support the characters. To work

around this issue, either rename the file after being restored or change the LANG variable on the Avamar server to the correct locale.

## Restore of files with special characters in file name when Avamar server LANG variable is not set

When the *LANG* variable is not set on an Avamar server, using Avamar Web Restore to restore a file with special characters in the file name fails. To fix this issue, set the *LANG* variable in `/etc/locale.conf` and reboot the Avamar server.

## Proper UI rendering on Internet Explorer 11 browser

High Security setting in Internet Explorer 11 prevents rendering of JavaScript commands in the Avamar Web Restore pages. To work around this issue, add the Avamar Web Restore server to the trusted sites list in Internet Explorer.

## Restore of large number of files

Users cannot restore a large number of files through Avamar Web Restore. Limit each restore task to fewer than 200 files.

## Backup client technical notes

The following technical notes apply to backup clients.

### Linux client installation binaries

Because of many compatible Linux operating systems, not all supported Linux operating systems have natively built installation binaries. The names of installation binaries do not always match the name of the operating system. For example, client installation binaries for Red Hat Enterprise Linux 6 are built on SUSE Enterprise Server 11. Refer to SLES 11 in the name of the installation binaries. However, these installation binaries are appropriate for installation on Red Hat Enterprise Linux 6.

### IPv6 not supported on HP-UX PA-RISC

Avamar support for IPv6 is not available for the HP-UX PA-RISC platform.

### Log files are time/date stamped in UTC time

Some client log and other files that are created in the VARDIR are time/date stamped in Universal Time Code (UTC) time (Greenwich Mean Time) and not the local time. This step can cause confusion when looking for a particular log file.

## Firewall software must be configured to allow communication with the Avamar server

Firewall software inherently interferes with communication between the Avamar server and Avamar clients by disabling inward connections to most data ports. Configure the firewall application to allow bi-directional communication between the Avamar client and the Avamar server when the following occurs:

- If firewall software is used on a client computer (for example, ZoneAlarm, Norton, McAfee).
- If the integrated firewall is used with Windows clients.

This step is accomplished by adding the Dell Client Agent to an “allowed” or “exceptions” list, which also depends on the firewall application. The documentation for the firewall should provide additional information.

## Avamar icon disappears from Mac system menu bar

On rare occasions, the Avamar icon disappears from the Mac system menu bar. To restore the icon, restart the Avamar client using the Avamar Client application launcher in the Applications folder.

## Standby, sleep, and hibernate states interfere with backups

Issues may occur when computers go into standby/sleep (ACPI state G1-S3), hibernate (ACPI state G1-S4), or hybrid sleep (Windows Vista) modes during a backup.

On returning to a working state (ACPI state G0-S0), the network connection between the client and the Avamar server may be lost and yet appear from the server. Canceling the backup from the client side has no effect.

To drop the backup connection, cancel the backup from the server side. This step occurs automatically when the connection is inactive for more than 1 hour.

To help minimize this problem, ensure that the BIOS and drivers on all supported computers are up-to-date.

## Browse of shared storage fails after failover in dual-stacked cluster environments

Shared storage cannot be browsed in a cluster by using the Avamar cluster client after a failover in a dual-stacked cluster environment. To enable browsing, rerun the Cluster Configuration Tool on the active node to remove and then reconfigure the Avamar cluster client.

## Backup cannot proceed when mandatory locks are encountered

Avamar client software honors all mandatory locks in the target file system on Solaris and HP-UX operating systems. However, this can cause backup operations to hang indefinitely when a mandatory lock is held by another application on files that Avamar is backing up.

To work around this issue, exclude all specified files and directories with mandatory locks from the backup dataset, and perform another backup.

## Solaris path length limitation

Solaris imposes a maximum path length limit of 1,023 characters. Therefore, paths cannot be specified for greater than 1,023 characters.

## Retention must expire before February 7, 2106 for 32-bit Windows and Linux clients

For backups of 32-bit Windows or 32-bit Linux client computers, do not assign a retention period for a date after February 7, 2106. If an extended retention period is assigned to a 32-bit Windows client, the backup completes with exceptions. For 32-bit Linux clients, the backups complete but do not appear in Avamar Administrator.

## Issues when running multiple CLI backup or restore operations at a time for a client

Stability issues occur when multiple command line interface (CLI) backup or restore operations are run at a time for a client. To work around this issue, perform only one CLI operation at a time for each client.

## Password best practices

The following technical notes provide best practices for creating and protecting passwords.

### Best practices for creating passwords

The following table provides best practices for creating passwords:



**Table 33. Best practices for creating passwords**

Best practice	Details
Do not use Personal Identifiable Information (PII).	Do not use PII in the password, such as: <ul style="list-style-type: none"> <li>• Your name</li> <li>• Your username</li> <li>• Your birthday</li> <li>• Names of pets</li> <li>• Names of your children</li> <li>• Name of your alma mater</li> <li>• Keywords that are associated with your hobbies</li> </ul>
Do not use words from the dictionary.	Do not use any word that can be found in the dictionary as your full password.
Use strong passwords.	Always use strong passwords when creating passwords. Strong passwords include: <ul style="list-style-type: none"> <li>• At least eight characters</li> <li>• Special characters such as a percent sign (%) or ampersand (&amp;)</li> <li>• Nonalphabetic characters</li> <li>• Both uppercase and lowercase characters</li> </ul>
Use different passwords for user accounts.	Always use a different password for each user account.
Change your password regularly.	<ul style="list-style-type: none"> <li>• Change your most critical passwords regularly.</li> <li>• Change your passwords at least every 6 months.</li> <li>• When you change your password, avoid using variations of a previous password.</li> <li>• Immediately change your password if you expect another person has access to your account, or knows your password.</li> <li>• Always change your password when you receive an account.</li> </ul>

## Password protection best practices

Create a password that you can remember without storing it anywhere. However, if the password must be stored, follow these recommendations:

- Use a password vault application to protect and help manage your passwords.
- If passwords must be written down on a piece of paper, store the paper in a secure place and destroy it when it is no longer needed.
- Do not put your username and password on a post it note under your keyboard.
- Do not write down your username and password in the same place.
- Use caution regarding where passwords are saved on systems. Some dialog boxes, such as those for remote access and other telephone connections, present an option to save or remember a password. Selecting this option poses a potential security threat.
- Never share your password with anyone and do not give your password to anyone over the phone.

## Documentation

The following sections describe the documentation and information products that are available with this release of Avamar:

### Avamar product documentation

The Avamar documentation set includes the following:

**Table 34. Avamar documentation set**

Document	Description
Avamar Administration Guide	This document describes how to configure, administer, monitor, and maintain the Avamar system.

**Table 34. Avamar documentation set (continued)**

Document	Description
Avamar Backup Clients User Guide	This document describes how to install and activate Avamar backup clients on all platforms. It also describes how to use the Avamar backup client to back up and restore data.
Avamar Fitness Analyzer User Guide	This document describes how to use the reporting and analysis software for Avamar servers .
Avamar Management Console Command Line Interface (MCCLI) Programmer Guide	This document describes how to install, configure, and use the Avamar Management Console Command Line Interface (MCCLI), which is a Java software application that provides command-line access to Avamar Administrator features.
Avamar NDMP Accelerator for NAS Systems User Guide	This document describes how to install and configure the Avamar NDMP Accelerator, and how to back up and restore data on supported Dell storage systems (Unity,VNX,Isilon), NetApp filers, and Oracle ZFS.
Avamar Operational Best Practices	This document provides best practices for designing, configuring, managing, and tuning the performance of the Avamar system.
Avamar Orchestra Getting Started Guide	This document provides an introduction to the Avamar Orchestra REST API for multisystems management, including the Orchestra web UI and the Swagger interface.
Avamar Plug-in for vCenter Administration Guide	This document describes how to install, configure, administer, and use the Dell Backup and Recovery plug-in for vCenter to back up and restore VMware image backups on an Avamar server.
Avamar Product Security Guide	This document discusses Avamar security considerations, including user authentication and authorization, client/server access and authentication, data security and integrity, system monitoring, server hardening, port usage, and firewall requirements.
Avamar Release Notes	This document describes new and changed features, resolved issues, known issues, and supplemental information about the latest Avamar release.
Avamar Reports Guide	This document describes how to create, manage, and interpret the information in Avamar reports.
Avamar Virtual Edition Installation and Upgrade Guide	This document describes how to install the Avamar Virtual Edition solution, a single-node, non-RAIN Avamar server that runs as a virtual machine in various environments.
Avamar and Data Domain System Integration Guide	This document provides best practices for designing, configuring, and managing Data Domain integration with the Avamar system.
Avamar for Exchange VSS User Guide	This document describes how to install Avamar in a Microsoft Exchange Server environment, and how to back up and restore data using Avamar with Microsoft Volume Shadow Copy Service (VSS) technology.
Avamar for Hyper-V VSS Guide	This document describes how to install Avamar in a Microsoft Hyper-V environment, and how to back up and restore virtual machines using Avamar with Microsoft Volume Shadow Copy Service (VSS) technology.
Avamar for IBM DB2 User Guide	This document describes how to install Avamar in an IBM DB2 environment and how to back up and restore DB2 databases.
Avamar for Lotus Domino User Guide	This document describes how to install Avamar in a Lotus Domino environment, and how to back up and restore data.
Avamar for Oracle User Guide	This document describes how to install Avamar in an Oracle database environment, and how to back up and restore Oracle databases.
Avamar for SAP with Oracle User Guide	This document describes how to install Avamar in an SAP environment with Oracle, and how to back up and restore SAP servers with Oracle databases.
Avamar for SQL Server User Guide	This document describes how to install Avamar in a Microsoft SQL Server environment, and how to back up and restore SQL Server databases.

**Table 34. Avamar documentation set (continued)**

Document	Description
Avamar for SharePoint VSS User Guide	This document describes how to install Avamar in a SharePoint environment, and how to back up and restore data using Avamar with Microsoft Volume Shadow Copy Service (VSS) technology.
Avamar for Sybase ASE User Guide	This document describes how to install Avamar in a Sybase environment, and how to back up and restore Sybase Adaptive Server Enterprise (ASE) databases.
Avamar for VMware User Guide	This document describes how to install, configure, and use Avamar to back up and restore virtual machines in a VMware environment.
Avamar for Windows Server User Guide	This document describes how to install the Avamar client for Microsoft Windows, and how to back up and restore data on a Windows server.

## Avamar related documentation

In addition to the product documentation, the following related links and documentation provide more information about Avamar:

### E-lab Navigator

The E-LAB Navigator provides server, client, and platform compatibility and interoperability information. See, the E-LAB Navigator at <https://elabnavigator.dell.com/eln/elhome>.

### Technical notes and white papers

Avamar technical notes provide technical details on specific product features, including step-by-step tasks, where necessary. White papers provide an in-depth technical perspective of a product or products as applied to critical business issues or requirements. Both technical notes and white papers are available on Online Support at <https://www.dell.com/support>.

## Installation and upgrade considerations

The following sections provide information about installation and supported upgrades in an Avamar environment:

### NOTE:

- The password complexity rules have changed in Avamar 19.10. See the *Avamar Product Security Guide* for more information about the password complexity.
- Use the Avamar Installation Manager (AVI) to download and install workflow packages. In the **Password Validation** tab of AVI, while entering the passwords ensure that the password length does not exceed more than 20 characters. If it exceeds the maximum characters that are allowed, you must change the password to proceed with the upgrade process. See the section "Changes in the password length" of the *Avamar Administration Guide* for the instructions to change the password.

## Avamar server and Avamar Virtual Edition installation and upgrade

For a physical Avamar server, a technical representative must perform the installation or upgrade. Downgrading the Avamar server software to an earlier version is not supported under any circumstances.

Support to upgrade Avamar from 7.5.1 with SLES version 11 SP1, SLES version 11 SP3, SLES version 11 SP4, SLES version 12 SP4, SLES version 12 SP5 to Avamar 19.10. This upgrade will also upgrade SLES to SLES 12 SP5, which is the required version for 19.4 and later release.

The client downloads, which provide the ability to download the current client versions from the server's **Documents and Downloads** web interface, are installed along with the server upgrade. The upgrade is provided by the Avamar Server Upgrade team unless a request is made that the team refrains from installing. However, the upgrade team does not install the Avamar Upgrade installers, which provide the client kits for the Avamar Client Manager's automated update feature. This option is a customer-upgradeable kit which can be obtained from the upgrade information. For instructions on application of the client

installers, see the *Avamar Client-Only System Upgrades Technical Note* available on the online support website at <https://dell.com/support/>.

AVE can be deployed using M5 instance in AWS. It can work normally after being deployed using M5 instance. The M5 instance is a Nitro-based instance. M5 instances are built on the AWS Nitro System and Elastic Block Storage (EBS) volumes are exposed as NVMe block devices on Nitro-based instance. The Nitro system is a collection of AWS- built hardware and software components which enable high performance, high availability, and high security. For more information, see the [Amazon EC2 M5 Instances](#).

To install a 16 TB AVE on Azure, customers must use the D14\_v2 instance type instead of A9 since A9 will no longer be supported by Azure.

To install a 0.5 TB or 2 TB AVE, support new instance type A2m\_v2.

## Upgrade requirements for Avamar

Review the requirements in the following sections before you upgrade to Avamar 19.10:

### Upgrade requirements in a VMware environment

Ensure that the VMware environment meets the following requirements when you upgrade to Avamar 19.10:

- Reboot proxy virtual machines after you upgrade the Avamar server.
- Ensure that the Avamar server time is synchronized with the ESXi host before upgrade. If the Avamar server is a configured NTP server, also ensure that the ESXi host time is synchronized with the same NTP server.

### Upgrade requirements for Avamar with a Data Domain system

The detailed information about the Avamar and Data Domain system compatibility is available in the E-LAB Navigator at <https://elabnavigator.dell.com/eln/elhome>.

The upgrade path for Avamar and Data Domain is specific. Failure to upgrade software in the proper order can cause Avamar maintenance functions and/or backups to fail. If this happens and the Avamar server fails, a rollback operation fails. The *Avamar and Data Domain System Integration Guide* provides details.

**NOTE:** Support to upgrade Avamar from 7.5.1 with SLES version 11 SP1, SLES version 11 SP3, SLES version 11 SP4, SLES version 12 SP4, or SLES version 12 SP5 to Avamar 19.4 and later. This upgrade will also upgrade SLES to SLES 12 SP5, which is the required version for 19.4 and later releases.

To upgrade Avamar with a Data Domain system:

1. Ensure that all Avamar clients are running on the latest version of Avamar client software.
2. Upgrade the Data Domain systems to DD OS 6.2 or later.
3. Upgrade the Avamar server to the latest version.

**NOTE:** If you fail to perform the upgrade steps or you perform the steps out of sequence, backup failures and data corruption on the backup device can occur. All Avamar and Data Domain upgrades should be planned ahead of time with the assistance of the Remote Proactive Avamar Upgrade team. Do not attempt to proceed without their assistance and planning.

## Where to get help

The Dell Technologies Support site (<https://www.dell.com/support>) contains important information about products and services including drivers, installation packages, product documentation, knowledge base articles, and advisories.

A valid support contract and account might be required to access all the available information about a specific Dell Technologies product or service.

## Troubleshooting and getting help

The Avamar support page provides access to licensing information, product documentation, advisories, and downloads, as well as how-to and troubleshooting information. This information may resolve a product issue before contacting Customer Support.

To access the Avamar support page:

1. Go to <https://www.dell.com/support>.
2. Type a product name in the **Enter a Service Tag, Serial Number, Service Request, Model, or Keyword** search box.
3. Select the product from the list that appears. When you select a product, the **Product Support** page loads automatically.
4. (Optional) Add the product to the **My Products** list by clicking **Add to My Saved Products** in the upper right corner of the **Product Support** page.

## Knowledgebase

The Knowledgebase contains applicable solutions that you can search for either by solution number (for example, KB000xxxxxx) or by keyword.

To search the Knowledgebase:

1. Go to <https://www.dell.com/support>.
2. Under the **Support** tab, click **Knowledge Base**.
3. Type either the solution number or keywords in the search box. Optionally, you can limit the search to specific products by typing a product name in the search box and then selecting the product from the list that appears.

## Online communities


Go to Community Network at <https://www.dell.com/community> for peer contacts, conversations, and content on product support and solutions. Interactively engage online with customers, partners, and certified professionals for all products.

## Live chat

To engage Customer Support by using live interactive chat, click **Join Live Chat** on the **Service Center** panel of the Avamar support page.

## Service requests

For in-depth help from Customer Support, submit a service request by clicking **Create Service Requests** on the **Service Center** panel of the Avamar support page.

 **NOTE:** To open a service request, you must have a valid support agreement. Contact a sales representative for details about obtaining a valid support agreement or with questions about an account.

To review an open service request, click the **Service Center** link on the **Service Center** panel, and then click **View and manage service requests**.

## Enhancing support

It is recommended to enable Dell Connectivity and Email Home on all Avamar systems:


- Dell Connectivity automatically generates service requests for high priority events. To configure Dell Connectivity, see *Avamar Administration Guide* for detailed steps.
- Email Home sends configuration, capacity, and general system information to Customer Support.

## Comments and suggestions

Feedback helps to improve the accuracy, organization, and overall quality of publications. Perform one of the following steps to provide feedback:

- Go to <https://contentfeedback.dell.com/s>, and submit a ticket.
- Send feedback to [DPADDocFeedback@dell.com](mailto:DPADDocFeedback@dell.com).

## Notes, cautions, and warnings

 **NOTE:** A NOTE indicates important information that helps you make better use of your product.

 **CAUTION:** A CAUTION indicates either potential damage to hardware or loss of data and tells you how to avoid the problem.

 **WARNING:** A WARNING indicates a potential for property damage, personal injury, or death.